

PANEL MOUNT INDICATOR, NON-RELAMPABLE

NEON AND INCANDESCENT TECHNOLOGY

MOUNTING HOLE, Ø 0.310"

| PART NO. | LENS COLOR | VOLTAGE | CURRENT [mA] | RATED LIFE HOURS |
|--------------------------------|------------|------------|--------------|------------------|
| NEON 115VAC SERIES | | | | |
| WL-2110A1 | RED | 105-125VAC | 1.5mA | 25,000 |
| WL-2110A2 | CLEAR | 105-125VAC | 1.5mA | 25,000 |
| WL-2110A3 | AMBER | 105-125VAC | 1.5mA | 25,000 |
| WL-2110A4 | WHITE | 105-125VAC | 1.5mA | 25,000 |
| WL-2112A5 | GREEN | 105-125VAC | 1.5mA | 25,000 |
| WL-2112A6 | BLUE | 105-125VAC | 1.5mA | 25,000 |
| NEON 230VAC SERIES | | | | |
| WL-2111A1 | RED | 208-250VAC | 1.5mA | 25,000 |
| WL-2111A2 | CLEAR | 208-250VAC | 1.5mA | 25,000 |
| WL-2111A3 | AMBER | 208-250VAC | 1.5mA | 25,000 |
| WL-2111A4 | WHITE | 208-250VAC | 1.5mA | 25,000 |
| WL-2113A5 | GREEN | 208-250VAC | 1.5mA | 25,000 |
| WL-2113A6 | BLUE | 208-250VAC | 1.5mA | 25,000 |
| INCANDESCENT 12V SERIES | | | | |
| WL-2195A1-12V | RED | 12V-14V | 80mA | 25,000 |
| WL-2195A3-12V | AMBER | 12V-14V | 80mA | 25,000 |
| WL-2195A4-12V | WHITE | 12V-14V | 80mA | 25,000 |
| WL-2195A5-12V | GREEN | 12V-14V | 80mA | 25,000 |
| INCANDESCENT 28V SERIES | | | | |
| WL-2195A1-28V | RED | 24V-28V | 40mA | 25,000 |
| WL-2195A3-28V | AMBER | 24V-28V | 40mA | 25,000 |
| WL-2195A4-28V | WHITE | 24V-28V | 40mA | 25,000 |
| WL-2195A5-28V | GREEN | 24V-28V | 40mA | 25,000 |

NOTES


1. Minimum panel thickness 0.030"
2. 6" leads with 1/2" strip are standard
3. Storage temperature
 T_{STG} : -25°C - +80°C
4. Ambient temperature
 T_A : -20°C - +60°C
5. Voltage tolerance
 V_{OP} : ±10%
6. AC operation only for neon type
7. AC/DC operation for incandescent type
8. Body material
Nylon, white
9. Lens material
Polycarbonate
10. Bezel material
Nylon, white
11. Wire gauge
18 AWG
12. Wire strip
1/2"

CERTIFICATIONS

UL (E340667), RoHS



DIMENSIONAL CHARACTERISTICS



unless otherwise specified, all dimensions are in inches



OPTIONS

Additional options and lens styles available. Please contact Wamco for more information.

