




---

 PRODUCT-DETAILS

## AFS52-30-22-13

### AFS52-30-22-13 100-250V50/60HZ-DC Contactor




---

**General Information**

Extended Product Type	AFS52-30-22-13
Product ID	1SBL367082R1322
EAN	3471523157736
Catalog Description	AFS52-30-22-13 100-250V50/60HZ-DC Contactor

Long Description	<p>The AFS52-30-22-13 is a 3 pole - 690 V IEC or 600 V UL contactor with fixed 2 N.O + 2 N.C. front mounted auxiliary contact blocks with screw connections, controlling motors up to 22 kW / 400 V AC (AC-3) or 40 hp / 480 V UL and switching power circuits up to 100 A (AC-1) or 80 A UL general use. AFS contactors can be easily integrated in machine manufacturer's systems complying with main standards EN ISO 13849 and EN 62061 - guaranteeing the safe use of your machinery and equipment. An easily identifiable yellow low energy auxiliary contact block ensures the status feedback circuits required in machine safety applications. Thanks to the AF technology, the contactor has a wide control voltage range (100 ... 250 V), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p>
------------------	--

---

**Ordering**

Minimum Order Quantity	1 piece
------------------------	---------

Customs Tariff Number

85364900

**Popular Downloads**

Data Sheet, Technical Information	1SBC100220C0201
Instructions and Manuals	1SBC101052M6801
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	DNV_TAE00001AF-4

**Dimensions**

Product Net Width	55 mm
Product Net Depth / Length	144 mm
Product Net Height	125.5 mm
Product Net Weight	1 kg

**Technical**

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	2
Number of Auxiliary Contacts NC	2
Number of Poles	3P
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-1:22, CSA C22.2 No. 60947-4-1:22
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I <sub>th</sub> )	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^\circ\text{C}$ 105 A acc. to IEC 60947-5-1, $\Theta = 40\text{ }^\circ\text{C}$ 16 A
Rated Operational Current AC-1 (I <sub>e</sub> )	(690 V) 40 °C 100 A (690 V) 60 °C 80 A (690 V) 70 °C 70 A
Rated Operational Current AC-3 (I <sub>e</sub> )	(415 V) 60 °C 53 A (440 V) 60 °C 53 A (500 V) 60 °C 45 A (690 V) 60 °C 35 A (380 / 400 V) 60 °C 53 A (220 / 230 / 240 V) 60 °C 53 A
Rated Operational Current AC-3e (I <sub>e</sub> )	(415 V) 60 °C 53 A (440 V) 60 °C 53 A (500 V) 60 °C 45 A (690 V) 60 °C 35 A (380 / 400 V) 60 °C 53 A (220 / 230 / 240 V) 60 °C 53 A
Rated Operational Current AC-15 (I <sub>e</sub> )	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A

	(400 / 440 V) 3 A
Rated Operational Current DC-1 ( $I_e$ )	(110 V) 2 Poles in Series, 40 °C 100 A (110 V) 2 Poles in Series, 60 °C 80 A (110 V) 2 Poles in Series, 70 °C 70 A (110 V) 3 Poles in Series, 40 °C 100 A (110 V) 3 Poles in Series, 60 °C 80 A (110 V) 3 Poles in Series, 70 °C 70 A (220 V) 3 Poles in Series, 40 °C 100 A (220 V) 3 Poles in Series, 60 °C 80 A (220 V) 3 Poles in Series, 70 °C 70 A (72 V) 1-Pole, 40 °C 100 A (72 V) 1-Pole, 60 °C 80 A (72 V) 1-Pole, 70 °C 70 A (72 V) 2 Poles in Series, 40 °C 100 A (72 V) 2 Poles in Series, 60 °C 80 A (72 V) 2 Poles in Series, 70 °C 70 A (72 V) 3 Poles in Series, 40 °C 100 A (72 V) 3 Poles in Series, 60 °C 80 A (72 V) 3 Poles in Series, 70 °C 70 A
Rated Operational Current DC-3 ( $I_e$ )	(110 V) 2 Poles in Series, 40 °C 100 A (110 V) 2 Poles in Series, 60 °C 80 A (110 V) 2 Poles in Series, 70 °C 70 A (110 V) 3 Poles in Series, 40 °C 100 A (110 V) 3 Poles in Series, 60 °C 80 A (110 V) 3 Poles in Series, 70 °C 70 A (220 V) 3 Poles in Series, 40 °C 100 A (220 V) 3 Poles in Series, 60 °C 80 A (220 V) 3 Poles in Series, 70 °C 70 A (72 V) 1-Pole, 40 °C 100 A (72 V) 1-Pole, 60 °C 80 A (72 V) 1-Pole, 70 °C 70 A (72 V) 2 Poles in Series, 40 °C 100 A (72 V) 2 Poles in Series, 60 °C 80 A (72 V) 2 Poles in Series, 70 °C 70 A (72 V) 3 Poles in Series, 40 °C 100 A (72 V) 3 Poles in Series, 60 °C 80 A (72 V) 3 Poles in Series, 70 °C 70 A
Rated Operational Current DC-5 ( $I_e$ )	(110 V) 2 Poles in Series, 40 °C 100 A (110 V) 2 Poles in Series, 60 °C 80 A (110 V) 2 Poles in Series, 70 °C 70 A (110 V) 3 Poles in Series, 40 °C 100 A (110 V) 3 Poles in Series, 60 °C 80 A (110 V) 3 Poles in Series, 70 °C 70 A (220 V) 3 Poles in Series, 40 °C 100 A (220 V) 3 Poles in Series, 60 °C 80 A (220 V) 3 Poles in Series, 70 °C 70 A (72 V) 1-Pole, 40 °C 100 A (72 V) 1-Pole, 60 °C 80 A (72 V) 1-Pole, 70 °C 70 A (72 V) 2 Poles in Series, 40 °C 100 A (72 V) 2 Poles in Series, 60 °C 80 A (72 V) 2 Poles in Series, 70 °C 70 A (72 V) 3 Poles in Series, 40 °C 100 A (72 V) 3 Poles in Series, 60 °C 80 A (72 V) 3 Poles in Series, 70 °C 70 A
Rated Operational Current DC-13 ( $I_e$ )	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Power AC-3 ( $P_e$ )	(400 V) 22 kW (415 V) 30 kW (440 V) 30 kW (500 V) 30 kW (690 V) 30 kW

	(380 / 400 V) 22 kW (220 / 230 / 240 V) 15 kW
Rated Operational Power AC-3e (P <sub>e</sub> )	(415 V) 30 kW (440 V) 30 kW (500 V) 30 kW (690 V) 30 kW (380 / 400 V) 22 kW (220 / 230 / 240 V) 15 kW
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 600 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 350 A for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 440 V 950 A cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 690 V 600 A
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	6 kV
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U <sub>c</sub> )	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Power Loss	at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 6.3 W at Rated Operating Conditions AC-3 per Pole 1.7 W
Operate Time	Between Coil De-energization and NC Contact Closing 19 ... 105 ms Between Coil De-energization and NO Contact Opening 17 ... 100 ms Between Coil Energization and NC Contact Opening 38 ... 95 ms Between Coil Energization and NO Contact Closing 42 ... 100 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M4 or 2 x M6 screws placed diagonally
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 4 ... 35 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 4 ... 35 mm <sup>2</sup> Rigid Stranded 1/2x 6 ... 35 mm <sup>2</sup>
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>
Wire Stripping Length	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 16 mm
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Tightening Torque	Auxiliary Circuit 1.2 N·m Control Circuit 1.2 N·m Main Circuit 4 N·m

Terminal Type	Screw Terminals
Product Name	Block Contactor

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 80 A
Horsepower Rating UL/CSA	(120 V AC) Single Phase 3 hp (200 ... 208 V AC) Three Phase 15 hp (220 ... 240 V AC) Three Phase 20 hp (240 V AC) Single Phase 10 hp (440 ... 480 V AC) Three Phase 40 hp (550 ... 600 V AC) Three Phase 50 hp
Connecting Capacity Main Circuit UL/CSA	Rigid Stranded 1/2x 10-2 AWG
Connecting Capacity Control Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 11 in-lb Control Circuit 11 in-lb Main Circuit 35 in-lb
Full Load Amps Motor Use	(120 V AC) Single Phase 34 A (200 ... 208 V AC) Three Phase 48.3 A (220 ... 240 V AC) Three Phase 54 A (240 V AC) Single Phase 50 A (440 ... 480 V AC) Three Phase 52 A (550 ... 600 V AC) Three Phase 52 A

## Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -40 ... 70 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: A 25 g Closed, Shock Direction: B1 25 g Closed, Shock Direction: B2 15 g Closed, Shock Direction: C1 25 g Closed, Shock Direction: C2 25 g
Resistance to Vibrations	3g Closed Position & 3g Open Position 5 ... 300 Hz
Pollution Degree	3

## Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## ABB EcoSolutions

ABB EcoSolutions	Yes
End Of Life Disassembling Instructions	1SBC101081M6801
Environmental Product Declaration - EPD	1SBD250584E1000
Sustainable Material Content in Packaging (wt. %)	FSC Recycled Paper - 94.6 %
Sustainable Material Content in Product (wt. %)	Recycled Metal - 28.2 %

## Certificates and Declarations

A2L Certificate – UL	9AKK108469A4890;9AKK108469A4892
ABS Certificate	ABS_20-2060694-PDA
BV Certificate	BV_2634H36994B1
CB Certificate	CB_SE-113324M1
CCC Certificate	CQC2015010304824714
CQC Certificate	CQC2015010304824714
Declaration of Conformity - CCC	2020980304001256
Declaration of Conformity - CE	1SBD250022U1000
Declaration of Conformity - UKCA	1SBD250044U1000
DNV Certificate	DNV_TAE00001AF-4
LR Certificate	LRS_LR23403517TA-02
RMRS Certificate	RMRS_1802705280
UL Certificate	UL-US-L312527-1141-10303102-9 UL-CA-L312527-4141-10303102-9
UL Listing Card	E312527

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	167 mm
Package Level 1 Depth / Length	180 mm
Package Level 1 Height	97 mm
Package Level 1 Gross Weight	1.14 kg
Package Level 1 EAN	3471523157736
Package Level 2 Units	box 6 piece
Package Level 2 Width	250 mm
Package Level 2 Depth / Length	300 mm
Package Level 2 Height	300 mm
Package Level 2 Gross Weight	6.84 kg
Package Level 3 Units	144 piece

## External Classifications and Standards

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4758 >> lec Contactors
E-Number (Finland)	3708069
E-Number (Sweden)	3210670

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SBN010120R1011	CAL4-11 Auxiliary Contact Block	CAL4-11	1	piece

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AFS Contactors → AFS52

