

AZ942H

16 AMP MINIATURE PC BOARD RELAY

FEATURES

- Extremely low cost
- 16 Amp switching capacity
- Proof tracking index (PTI/CTI) 250
- Clearance and creepage distance >2.5 mm
- Class F insulation (155 °C) available
- Meets IEEE 587 6 kV lightning surge
- UL, CUR file E44211



CONTACTS

Arrangement	SPST (1 Form A) SPDT (1 Form C)
Ratings	Resistive load:
1 Form A	Max. switched power: 280 W or 4000 VA Max. switched current: 16 A Max. switched voltage: 28 VDC or 250 VAC
1 Form C	Max. switched power: 196 W or 2500 VA Max. switched current: 12 A Max. switched voltage: 28 VDC or 250 VAC
Rated Load UL	1 Form A 16 A at 250 VAC, resistive, 85°C, 50k cycles [2] 12 A at 250 VAC, resistive, 85°C, 100k cycles [2] 10 A at 277 VAC, resistive, 85°C, 25k cycles [2], [1] 10 A at 28 VDC, resistive, 85°C, 100k cycles [2], [1] 1/2 HP at 125 / 250 VAC [2] 1 Form C 16 A at 250 VAC, resistive, 85°C, 50k cycles (N.O.) [2] 12 A at 250 VAC, resistive, 85°C, 100k cycles (N.O.) [2] 12 A at 125 VAC, resistive, 85°C, 100k cycles (N.O.) [2], [1] 12 A at 125 VAC, resistive, 85°C, 100k cycles (N.C.) [2] 7 A at 277 VAC, resistive, 85°C, 100k cycles [2], [1] 7 A at 28 VDC, resistive, 85°C, 100k cycles [2], [1] 1/2 HP at 125 / 250 VAC [2] 4 FLA / 4 LRA at 240 VAC (N.O.) [2] 2 FLA / 4 LRA at 240 VAC (N.C.) [2]
Material	Silver cadmium oxide [1] or Silver tin oxide [2]
Resistance	< 100 milliohms initially

NOTES

1. All values at 20°C (68°F)
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1 x 10 ⁷ 1 x 10 ⁵ at 10A 250 VAC Res.
Operate Time (typical)	10 ms at nominal coil voltage
Release Time (typical)	5 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	2000 Vrms contact to coil 750 Vrms across contacts
Insulation Resistance	100 megohms min. at 20°C, 500 VDC, 50% RH
Insulation (according to DIN VDE 0110, IEC 60664-1)	Overvoltage category: II Pollution degree: 2 Nominal voltage: 250 VAC
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating	At nominal coil voltage Class B: -40°C(-40°F) to 70°C(158°F) Class F: -40°C(-40°F) to 85°C(185°F)
Storage	-40°C(-40°F) to 105°C(221°F)
Vibration	0.062" (1.5 mm) DA at 10–55Hz
Shock	10 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	13 g
Packing unit in pcs	20 per plastic tube / 1000 per carton box

COIL

Power At Pickup Voltage (typical)	230 mW
Max. Continuous Dissipation	Class B: 1.7 W at 20°C (68°F) ambient Class F: 2.2 W at 20°C (68°F) ambient
Temperature Rise	26°C (47°F) at nominal coil voltage
Temperature	Class B: Max. 130°C (221°F) Class F: Max. 155°C (311°F)

AZ942H

RELAY ORDERING DATA

STANDARD RELAYS				ORDER NUMBER*	
COIL SPECIFICATIONS				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance Ohm $\pm 10\%$	Form A (SPST-N.O.)	Form C (SPDT)
3	2.4	6.5	25	AZ942H-1A-3D	AZ942H-1C-3D
5	4.0	11.0	70	AZ942H-1A-5D	AZ942H-1C-5D
6	4.8	13.0	100	AZ942H-1A-6D	AZ942H-1C-6D
9	7.2	20.0	225	AZ942H-1A-9D	AZ942H-1C-9D
12	9.6	26.0	400	AZ942H-1A-12D	AZ942H-1C-12D
18	14.4	39.0	900	AZ942H-1A-18D	AZ942H-1C-18D
24	19.2	52.0	1,600	AZ942H-1A-24D	AZ942H-1C-24D
48	38.4	104.0	6,200	AZ942H-1A-48D	AZ942H-1C-48D

* For epoxy sealed version, add suffix "E." For silver tin oxide contacts add suffix "T." To indicate Class F version, add suffix "F."

IEEE STANDARD 587-1980 (ANSI/IEEE C62.41-1980) SURGE VOLTAGE WITHSTAND RATING

Test	Rating	Description
1.2 x 50 usec positive pulse	6 kV	Contact to coil – 5 pulses
1.2 X 50 usec negative pulse	6 kV	Contact to coil – 5 pulses
0.5 us 100 kHz ring wave	6 kV	Contact to coil - 5 waves

MECHANICAL DATA

Dimensions in inches with metric equivalents in parentheses. Tolerance: ± 0.010 "

PC BOARD LAYOUT

VIEWED TOWARDS TERMINALS

WIRING DIAGRAMS

FORM A FORM C

VIEWED TOWARDS TERMINALS

Dimensions in inches with metric equivalents in parentheses. Tolerance: ± 0.010 "

AMERICAN ZETTLER, INC.

11/14/18

PHONE: (949) 831-5000

www.azettler.com

E-MAIL: SALES@AZETTLER.COM

This specification provides an overview of the most significant part features. Any individual applications and operating conditions are not taken into consideration. It is recommended to test the product under application conditions. Responsibility for the application remains with the customer. Proper operation and service life cannot be guaranteed if the part is operated outside the specified limits.