



Drawings not to scale  
All dimensions in mm (inches) nominal

## SPECIFICATION

CONTACT FORM			A
CONTACT MATERIAL			Rhodium
SWITCHING CAPACITY	Max.	W/VA	10
SWITCHING VOLTAGE	Max.	Vac/dc	100
SWITCHING CURRENT	Max.	A	0.2
CARRYING CURRENT	Max.	A	0.5
DIELECTRIC STRENGTH	Min.	Vdc	150
CONTACT RESISTANCE	Max.	m $\Omega$	100
INSULATION RESISTANCE	Min.	$\Omega$	10 <sup>9</sup>
PULL-IN SENSITIVITY		AT	15 - 45
DROP-OUT SENSITIVITY	Min.	AT	DO/PI $\geq$ 0.8
SWITCHING TIME WITHOUT BOUNCE	Max.	ms	1.4
BOUNCE TIME	Max.	ms	1.0
RELEASE TIME	Max.	ms	0.05
RESONANT FREQUENCY	Typ.	Hz	3900
OPERATING FREQUENCY	Max.	Hz	500
VIBRATION	10-1000	Hz	20
SHOCK		G	30
CAPACITANCE	Typ.	pF	0.5
OPERATING TEMP. RANGE	Deg.	$^{\circ}$ C	-40 +125
TEST COIL	Type		0221

Close-differential switches

### We can supply custom cut and formed switches

NOTE: When cutting or bending switch leads it is important that the glass seal is not damaged. The cutting or bending point should be no closer than 3mm (.118) to the glass to metal seal and the lead should be supported between the cutting or bending point and the glass to metal seal.

Ordering Information			
Part Number	15	45	
Type	2212		
Maximum (AT) Sensitivity			
Minimum (AT) Sensitivity			

Example: Type 2212 Standard Sensitivity. Pull-in sensitivity between 20-30 AT is PART NO: 2212 20 30

## REED SWITCHES - Dry Contact

PART NUMBER  
**2212**

Rev. No.	Revision Note	Date	Signature
A	Web Site 2000	1-1-00	RG

The Comus Group of Companies

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and details of our full design and manufacturing service. All products are supplied to our standard conditions of sale otherwise agreed in writing.