


ST Series Relay Sockets

- Description** 8 and 11 Pin Square Base Sockets, DIN Rail Mountable
- Electrical Rating** • 300 Volts, 15 Amps
- Construction**
- Contacts** • Brass, Nickel Plated
 - Screws** • Binder Head, 6 - 32 x 1/4" Steel, Zinc Plated
 - Pressure Clamp, 6 - 32 x 5/16" Steel, Zinc Plated, Wire Range #12 - #20 Solid or Stranded
 - Molding** • Break Resistant Thermoplastic Black Standard, Grey Available
- Agency Approvals** • UL recognized, File No. E60008
- CSA certified, File No. LR29513
 - CE
 - ROHS







ST Series Ordering Code

Part #	Description	Terminal Type
ST08	DPDT, 8 Pin Blade	Binder Head Screws
ST08-PC	DPDT, 8 Pin Blade	Pressure Clamp Screws
ST11	3PDT, 11 Pin Blade	Binder Head Screws
ST11-PC	3PDT, 11 Pin Blade	Pressure Clamp Screws

Accessories

Part #	Description
	(Refer to the accessories pages 24-31)
C-103-PM	Prepunched Aluminum DIN Rail (1 Meter Lengths)
C-108-PM	Prepunched Raised Aluminum DIN Rail (1 Meter Lengths)
C-108-2PM	Prepunched Raised Aluminum DIN Rail (2 Meter Lengths)
HDB-8	Hold Down Spring

TERMINAL LOCATIONS



ST Series Note:

Terminals 2, 5 and 8 omitted on DPDT, 8 Pin models