

# Photocontrol - Button Thermal Photocontrol, 347 V

## Item K4027



#### **PRODUCT DESCRIPTION**

These photocontrols install within lighting fixtures, post lamps, or in-wall boxes to provide dusk-to-dawn ON/OFF control of outdoor lighting.

### **FEATURES**

- ► Mechanical bimetal switch with Cadmium Sulfide photocell
- ► Compact size fits into standard outlet box, post lamp, wall pack and other lighting fixtures
- ► Delay feature prevents unwanted OFF switching
- ▶ 3/8"-18 NPSM, 3/4" long stem with locking nut and washer gasket

#### **APPLICATIONS**

► Outdoor Lighting Control



# TECHNICAL DATA

General	
Model Number	K4027
Description	Button Thermal Photocontrol, 347 V
UPC Code	078275091672
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited
Usage Environments	Outdoor
Photocontrol Type	Thermal
Expected Lifetime (Years)	5
Expected Lifetime (Operations)	3650
Application Compatibilities	HID; Fluorescent; Incandescent
Photocontrol Style	Button
Photocontrol Sensor Location	Front

Control Specifications	
Sensor Time Delay	30 sec to 90 sec
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Activation On	1 to 5 fc
Activation Off	3 to 15 fc

Dimensions	
Product Height (in)	1 13/16
Product Height (mm)	46
Product Width (in)	15/16
Product Width (mm)	23.8
Product Depth (in)	13/16



Product Depth (mm)	20.6
Wire Lead Length (in)	9
Wire Lead Length (mm)	228.6
Wire Size Max	#18 AWG

Material Specifications		
Cover Color	Gray	
Housing Material	Polycarbonate	

Load Ratings	
Magnetic Ballast Range(s)	8.3 A, 2880 VA
Tungsten Range(s)	15 A, 5205 W

Electrical Specifications	
Wiring Option	Wire leads
Input Voltage Range(s)	347 VAC, 50/60 Hz

Packaging		
	Shipping Weight (lbs)	0.25
	Unit Carton Dimensions (H x W x D) in	4.88 x 1.75 x 3 in

Environmental Specifications		
Temperature (operation)	-40°C70°C	
Standards and Certifications		

Standards and Certifications	
CSA Certification	CSA
Other Certifications and Compatibilities	Title 20
California Proposition 65	DEHP
PDF Standards And Certifications	CSA; Title 20
Epi Certifications	CSA; Title 20



### **ACCESSORIES**



6LV1352 Light Shield Accessory for EK4036S, EK4436SM, K4000 Series Button Photocontrols



K43-WP-KIT Wall Plate Kit for EK4036S, K4000 Series Button Photocontrols



LGLBL
Lens Sticker Accessory for EK4000 & K4000 Series
Photocontrols