

Photocontrol - Locking Type Receptacle, 3-Pin, C136.10 Compliant, with Pole Mounting Bracket

Item K122



PRODUCT DESCRIPTION

The K122 NEMA receptacles provide the connector interface for locking type photocontrols. They can be installed in the light fixture itself, or attached externally with the use of a mounting bracket (included).

FEATURES

- ▶ NEMA receptacle with 3-prong sockets
- ▶ Compliant to ANSI C136.10 specifications

TECHNICAL DATA

General

Model Number	K122
Description	Locking Type Receptacle, 3-Pin, C136.10 Compliant, with Pole Mounting Bracket
UPC Code	078275501201
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Dimensions

Product Height (in)	2.13
Product Height (mm)	54.1
Product Diameter (in)	2.56
Product Diameter (mm)	65.02

Material Specifications

Color	Black
Base Material	Phenolic
Bracket Material	Aluminum
Back Cover Material	Phenolic
Power Contacts Material	Brass/Phosphor Bronze
Gasket	(Integrated) Thermal Elastomer
Wire Leads	#14 AWG, 105°C, AWM3321

Electrical Specifications

Power Contacts Rating	480 V max, 15 A max
-----------------------	---------------------

Packaging

Shipping Weight (lbs)	0.35
Unit Carton Dimensions (H x W x D) in	6.381 x 3.251 x 3.251 in

Environmental Specifications

Temperature (operation)	-40°C..80°C
-------------------------	-------------

Standards and Certifications

UL Certification	cULus
CSA Certification	CSA C22 No. M1986
Other Certifications and Compatibilities	Title 20; cRUus; Ansi C136.10
UL Standard	UL 772
California Proposition 65	DEHP
PDF Standards And Certifications	cULus; Title 20; cRUus
Epi Certifications	cULus; Title 20; cRUus