

Surge Protection Device - Surge Protective Device, 7-Mode, 120/208 VAC 3Ph Y, Type 1, Surge Current Rating 200kA

Item H20S13Y1DG1



PRODUCT DESCRIPTION

Intermatic PanelGuard Surge Protective Devices are designed to react quickly and eliminate surges providing optimal protection to downstream equipment. PanelGuard Industrial/Commercial-grade series are Parallel Connected Surge Protective Devices designed to protect all types of loads fed from individual disconnects, sub-panels, distribution panels and service entrance locations.

FEATURES

- ▶ Type 1 surge protection
- ▶ Optional audible alarm and dry relay contacts
- ▶ 7 Modes of protection
- ▶ NFPA 780, UL 96A Lightning system protection compliant
- ▶ NEMA 4X enclosure for indoor or outdoor installation
- ▶ Individually integrated disconnect TPMOV surge protection technology
- ▶ Blue LED status indicator per phase, red LED service indicator

APPLICATIONS

- ▶ Distribution Panel
- ▶ Service Entrance

TECHNICAL DATA

| General | |
|--|--|
| Model Number | H20S13Y1DG1 |
| Description | Surge Protective Device, 7-Mode, 120/208 VAC 3Ph Y, Type 1, Surge Current Rating 200kA |
| UPC Code | 078275152236 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | U.S.A. |
| Warranty Period | 10-Year limited |
| Surge Protection Type | 1 |
| Electrical Specifications | |
| Modes of Protection | 7 |
| Short Circuit Current Rating | 200 kA |
| Nominal Discharge Current | 20 kA |
| Maximum Surge Current Rating Per Phase | 200 kA |
| Maximum Surge Current Rating Per Mode | 100 kA |
| Surge Protection Technology | Individually integrated thermal disconnect technology TPMOV |
| Maximum Continuous Operating Voltage (L-G) | 150 |
| Maximum Continuous Operating Voltage (L-L) | 300 |
| Maximum Continuous Operating Voltage (L-N) | 150 |
| Maximum Continuous Operating Voltage (N-G) | 150 |
| Voltage Protection Rating (L-G) | 700 |
| Voltage Protection Rating (L-L) | 1000 |
| Voltage Protection Rating (L-N) | 700 |
| Voltage Protection Rating (N-G) | 700 |

Voltage 120/208 VAC 3-Phase Wye

Control Specifications

Surge Protection LED Indicator Yes

Mechanical Specifications

Enclosure Type NEMA Type 4X

Dimensions

Product Dimensions (H x W x D) in 10.59 x 5.25 x 3.29 in

Wire Lead Length (in) 18"

Wire Size Max #10 AWG

Conduit Size 3/4"

Material Specifications

Color Gray

Product Weight (kg) 0.27

Product Weight (lbs) 0.6

Diagnostics Monitoring

Diagnostics Indicator Blue LED Status Indicator Per Phase; Red LED Service Indicator

Benefits

Filter No Filter

Packaging

Shipping Weight (lbs) 0.6

Unit Carton Dimensions (H x W x L) in 4.375 x 6.375 x 12.625 in

Environmental Specifications

Temperature (operation) -40 °F to 176 °F / (-40 °C to 80 °C)

Standards and Certifications

UL Certification ANSI/UL 1449 4th Edition

CSA Certification CSA C22.2 No. 269.1-14 (VZCA, VZCA7)

Other Certifications and Compatibilities 2020 National Electric Code, Article 242 (previously NEC, Art. 285), 700.10 & 708.20; ANSI/IEEE C62.72-2016, ANSI/IEEE C62.41.1, C62.41.2-2002; C62.45-2002, ANSI/IEEE C62.62-2010 environments: Categories: A, B & C; NFPA 780 & UL 96A Lightning protection systems

California Proposition 65 Lead

RoHS Certification Yes

DRAWINGS AND DIAGRAMS

