

## Surge Protection Device - Surge Protective Device, 4-Mode, 440/480 VAC 3Ph High Leg Delta, Type 1, Surge Current Rating 100kA

Item L10F13N4DG1



### PRODUCT DESCRIPTION

Intermatic PANELGUARD® Surge Protective Devices are designed to react quickly and eliminate surges providing optimal protection to downstream equipment. PANELGUARD Industrial/Commercial-grade series are Parallel Connected Surge Protective Devices designed to protect all types of loads fed from individual disconnects, sub-panels, distribution panels and service entrance locations.

### FEATURES

- ▶ Type 1 surge protection
- ▶ Optional audible alarm and dry relay contacts
- ▶ 4 Modes of protection
- ▶ NEMA 4X enclosure for indoor or outdoor installation
- ▶ Individually integrated disconnect TPMOV surge protection technology
- ▶ Blue LED protection status indicator, and red LED service indicator

### APPLICATIONS

- ▶ Distribution Panel
- ▶ Service Entrance

### TECHNICAL DATA

General	
Model Number	L10F13N4DG1
Description	Surge Protective Device, 4-Mode, 440/480 VAC 3Ph High Leg Delta, Type 1, Surge Current Rating 100kA
UPC Code	078275151871
Brand	Intermatic
Country of Origin (Intermatic)	U.S.A.
Warranty Period	5-Year limited
Surge Protection Type	1
Electrical Specifications	
Modes of Protection	4
Short Circuit Current Rating	200 kA
Nominal Discharge Current	20 kA
Maximum Surge Current Rating Per Phase	100 kA
Maximum Surge Current Rating Per Mode	100 kA
Surge Protection Technology	Individually integrated thermal disconnect technology TPMOV
Maximum Continuous Operating Voltage (L-G)	552
Maximum Continuous Operating Voltage (L-L)	552
Voltage Protection Rating (L-G)	1800
Voltage Protection Rating (L-L)	4000
Voltage	440/480 VAC 3-Phase High Leg Delta
Control Specifications	
Surge Protection LED Indicator	Yes

### Mechanical Specifications

Enclosure Type	NEMA Type 4X
----------------	--------------

### Dimensions

Product Dimensions (H x W x D) in	10.59 x 5.25 x 3.29 in
Wire Lead Length (in)	18"
Wire Size Max	#10 AWG
Conduit Size	3/4"

### Material Specifications

Color	Gray
Product Weight (kg)	0.27
Product Weight (lbs)	0.6

### Diagnostics Monitoring

Diagnostics Indicator	Blue LED Protection Status Indicator; Red LED Service Indicator
-----------------------	---

### Benefits

Filter	No Filter
--------	-----------

### Packaging

Shipping Weight (lbs)	0.6
Unit Carton Dimensions (H x W x L) in	4.375 x 6.375 x 12.625 in

### Environmental Specifications

Temperature (operation)	-40 °F to 176 °F / (-40 °C to 80 °C)
-------------------------	--------------------------------------

### Standards and Certifications

UL Certification	ANSI/UL 1449 4th Edition
CSA Certification	CSA C22.2 No. 269.1-14 (VZCA, VZCA7)
Other Certifications and Compatibilities	2020 National Electric Code, Article 242 (previously NEC, Art. 285), 700.10 & 708.20; ANSI/IEEE C62.72-2016, ANSI/IEEE C62.41.1, C62.41.2-2002; C62.45-2002, ANSI/IEEE C62.62-2010 environments: Categories: A, B & C
California Proposition 65	Lead
RoHS Certification	Yes

**DRAWINGS AND DIAGRAMS**

