

Weather Proof Cover - Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.25" Bronze

Item WP5000BR



c 🖤 us 🖉

FEATURES

- ► Complies with 2020 NEC Article 406.9 (B)(1) for wet locations and extra-duty applications
- CEC Article 26-702 Compliant
- ► UL Certified for Type 3R outdoor enclosures
- ► Meets requirements for cold impact testing: -60° F (-51° C)
- Heavy-duty UV stabilized polycarbonate cover, mounting base, and inserts
- $\blacktriangleright~$ 1/8" (3 mm) thick, neoprene gasket with slits for mounting screws
- ► Lockable hasp: All models accept up to 1/4" (6 mm) dia shank
- Impact rated: 12 lbf. impact test to ensure cover remains intact
- Reinforced hinge pin designed to exceed 40 lbf. hinge hang/stress test
- ► Warranty: 1-year limited
- ► NEW Faster Installation, Pre-Set for GFCI, No insert required
- Two inserts provided with all models that allow each model to meet multiple installations (up to 16 configurations)
- ► Max cord size: (2) #14 AWG or (1) #12 AWG

APPLICATIONS

► Receptacle Protection

TECHNICAL DATA


General	
Model Number	WP5000BR
Description	Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.25" Bronze
UPC Code	078275145542
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Mechanical Specifications	
Number of Included Inserts	3
Insert Types Included	WP17
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	Yes
Dimensions	
Product Dimensions (H x W x D) in	6 1/3 x 4 2/3 x 2 1/4 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Box Type	Single
Material Specifications	
Color	Bronze
Weatherproof Cover Material	UV Stabilized Plastic
Packaging	
Shipping Weight (lbs)	0.5
Unit Carton Dimensions (H x W x L) in	6.5 x 2.75 x 4.75 in



Standards and Certifications		
UL Certification	cULus	
CSA Certification	cCSAus	
California Proposition 65	None	



DRAWINGS AND DIAGRAMS





ACCESSORIES



WP17 Single-Gang Inserts (3)