

## In-Wall Timer - Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 5 Minute Max, Without Hold, Ivory

Item FD5M



### PRODUCT DESCRIPTION

The FD Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multi-gang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

### FEATURES

- ▶ 5-Minute timer
- ▶ SPST (Single-Pole Single-Throw)
- ▶ No electricity required to operate
- ▶ Replaces any standard or decorator single- or multi-gang wall switch
- ▶ Automatically limits ON time for energy consuming loads
- ▶ Quick and easy installation
- ▶ Time-saving up front terminal connection with teeter-type terminals
- ▶ Breaks circuit at end of timing cycle
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ No neutral connection is required
- ▶ Decorator switch plate not included
- ▶ Operates in temperatures down to -40° C

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Motor Control
- ▶ Air Movement & Ventilation

### TECHNICAL DATA

| General                        |   |
|--------------------------------|---|
| Model Number                   | FD5M  |
| Description                    | Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 5 Minute Max, Without Hold, Ivory |
| UPC Code                       | 078275185500  |
| Brand                          | Intermatic  |
| Country of Origin (Intermatic) | TUNISIA   |
| Warranty Period                | 1-Year limited  |
| Application Compatibilities    | Incandescent; Fluorescent; CFL; LED   |
| Harmonized Code                | 9107.00.4080  |
| Control Specifications         |   |
| Operation Mode                 | Countdown   |
| Countdown Time                 | 5 min   |
| Hold Mode Included             | No  |
| Mechanism Type                 | Analog/Mechanical   |
| Mechanical Specifications      |   |
| Wall Plate Configurations      | Single-Gang; Multi-Gang   |

**Dimensions**

Product Dimensions (H x W x D) in 4.125 x 1.75 x 1.25 in

**Material Specifications**

Color Ivory

**Load Ratings**

Resistive Heater 20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC

Tungsten (Incandescent) Range(s) 7 A, 125 VAC, 50/60 Hz, 875 W

Motor Load Ratings Ranges 1 HP, 125 VAC; 2 HP, 250 VAC

**Electrical Specifications**

Input Voltage Range(s) 125-277 VAC, 50/60 Hz

Wiring Configurations Single

Switch Type SPST

Neutral Connection Required No

**Environmental Specifications**

Temperature (operation) 32 - 104 °F / 0 - 40 °C

**Packaging**

Shipping Weight (lbs) 0.299

Unit Carton Dimensions (H x W x D) in 4.63 x 2.13 x 2.88 in

**Standards and Certifications**

CSA Certification cCSAus

Other Certifications and Compatibilities RU

California Proposition 65 DEHP

---

## ACCESSORIES



146MT573  
Knob-Wall Switch FD Series - Ivory



146MT574  
Knob-Wall Switch FD Series - White



146MT575  
Knob-Wall Switch FD Series - Almond



148FD5064  
Plate for 5-Min without HOLD, Ivory (FD5M)