

Occupancy Sensor - Commercial Grade Self-Adaptive In-Wall PIR Occupancy/Vacancy Sensor, No Neutral Required, Ivory

Item IOS-DSR-IV





### PRODUCT DESCRIPTION

The passive infrared sensors work by detecting the difference between heat emitted from the human body in motion and the background space. The sensor switch can turn a load ON and hold it as long as the sensor detects occupancy. After no motion is detected for the set time delay, the load turns OFF automatically. The sensor switch has one relay (equal to single pole switch), it also includes Auto Set and Walk Through features.

#### **FEATURES**

- ► Passive Infrared (PIR) sensing for presence detection
- ► Coverage: 180°, 1200 ft2 with non-obstructed views
- ► User-selectable Vacancy or Occupancy switch mode
- ► Zero-crossing technology for long life and performance
- ► Automatic self-adaptive time delay based on occupancy patterns
- ► IOS-DSR/DDR models feature optional walk-through detection mode
- ► Adjustable ambient light sensor override
- Incandescent/Fluorescent/CFL/LED compatible
- ► IOS-DOV models require a neutral connection
- Fits standard decorator wall plate (included)

#### **APPLICATIONS**

► Indoor Sensing Control

## TECHNICAL DATA

General	
Model Number	IOS-DSR-IV
Description	Commercial Grade Self-Adaptive In-Wall PIR Occupancy/Vacancy Sensor, No Neutral Required, Ivory
UPC Code	078275125193
Brand	Intermatic
Warranty Period	5-Year limited
Country of Origin (Intermatic)	CHINA
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Market	Commercial; Industrial; Residential; Utility

Control Specifications	
Sensor Switch Type	Occupancy; Vacancy
Sensor Technology	PIR (Passive Infrared); Zero-crossing
Adjustable Time Delay Min	15 sec
Adjustable Time Delay Max	30 min
Adjustable Light Level Min	30 lux
Adjustable Light Level Max	Daylight
Has Walk-Through Detection	Yes
PIR Coverage Area (sq ft)	1200

Mechanical Specifications
---------------------------

Mount Type In-Wall



PIR Coverage Pattern (degrees)	180
Maximum Mounting Height (ft)	A ft

Dimensions		
Product Height (in)	2.625	
Product Height (mm)	67	
Product Width (in)	1 5/16	
Product Width (mm)	33	
Product Depth (in)	1.75	
Product Depth (mm)	44	

# Material Specifications Color Ivory Includes Wall Plate Yes

Load Ratings	
Electronic Ballast LED	800 VA, 120 VAC; 1600 VA, 277 VAC
Resistive Load Ratings Ranges	800 W, 120 VAC
Inductive Load Ratings Ranges	800 VA, 120 VAC; 1600 VA, 277 VAC
Motor Load Ratings Ranges	1/4 HP
Ballast Fluorescent Ranges	800 VA, 120 VAC; 1600 VA, 277 VAC
Tungsten (Incandescent) Range(s)	800 W, 120 VAC
Resistive Heater	10 A

Electrical Specifications		
Input Voltage Range(s)	120/277 VAC, 50/60 Hz	
Occupancy Sensor Power Type	Line Voltage	
Number of Circuits	1	

Packaging	
Shipping Weight (lbs)	0.4
Shipping Weight (kg)	0.181
Unit Carton Dimensions (H x W x L) in	5 x 2.25 x 3 in

Environmental Specifications	
Temperature (operation)	32 - 131°F / 0 - 55°C

tandards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	Title 20
California Proposition 65	None