

Product data sheet

Specifications



Socket, SE Relays general purpose relay accessory, SPDT, 10A, 300 V, 5 pins, pins for printed circuit board, 781R series

70-781T-1

Main

Product Range	Legacy
Product Type	Socket
Product Compatibility	relay 781XAXR
Number of Terminals	5
Switch Function	SPDT
Contact Composition	1 NC + 1 NO

Complementary

Rated Current	10 A 300 V 15 A 150 V
[Ue] rated operational voltage	300 V
Contact Terminal Arrangement	Mixed
Connections Terminals	pins for printed circuit board
Fixing Mode	By screws, for printed circuit boards
Product Weight	0.63 oz (18 g)
Width	0.71 in (18 mm)
Depth	1.22 in (31 mm)

Environment

Ambient Air Temperature for Storage	-40...221 °F (-40...105 °C)
Ambient Air Temperature for Operation	-40...131 °F (-40...55 °C)
Flame Retardance	UL94-V0
Product Certifications	UL CE

Ordering and shipping details

GTIN	3606480278082
------	---------------

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the
---------------------------	---

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Approximate Dimensions

