

**Terminal blocks**

to Type 373

ASP051 page 47


**Type 373**

Header, centerline 2.5 mm / 0.098 inches, vertical mounting, square contact pins 0.8 mm / 0.031 inches, closed ends

**Technical Data**

	V / A	150 / 5
		130 V / 2.5 kV / 4 A
Insulation co-ordination according to IEC 664-1		
Clearance and creepage distances	min. 1.7 mm	
Insulating material class	CTI 600	
Overtoltage category	III	III II
Pollution degree	3	2 2
Rated voltage	80	320 320
Rated test voltage	0.8	4 2.5
Protection category according to IEC 529	IP00	
Solder pin dimension	0.8 x 0.8 mm	
Recommended pc board hole dia.	Ø 1.3 mm	
Solder pin length	3.2 mm	
Pole size	2 - 12	
Color	green	

Dimensions in mm 1 mm = 0.0394 in.



$L = (\text{pole size} - 1) \times \text{centerline} + 4.4 \text{ mm} / 0.173 \text{ inches}$

**Part numbers (P/N)**

(informations: page 111)

Complete the part number by adding the pole size.

**Type 373**

centerline 2.5 mm / 0.098 inches

P/N 313731



	02	03	04	05	06	07	08
09	10	11	12				

- Standard pole sizes
- Available on demand. Minimum order quantity 5000 pieces per item.