


1133.2

PTK 10/QT/STB BG

PTK 10/QT/STB BG



M4



Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm<sup>2</sup>, Width: 8 mm, Colour: Beige

## Business data

Product description	Test disconnect terminal
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	28
Weight per piece (including packaging)	29.74
Unit of weight	G
Customs number	85369010
Country of origin	DE

**1133.2**

**PTK 10/QT/STB BG**

**PTK 10/QT/STB BG**

## Technical Data

---

### Dimensions

---

Length	72 mm
Width	8 mm
Height TS 35/7.5	47 mm
Height TS 32	51.5 mm

### Ratings

---

Rated voltage	400 V
Rated current	10 A
Rated cross-section	10 mm <sup>2</sup>
Rated impulse voltage	4 kV
Overvoltage category	III
Contamination degree	3

**1133.2**

**PTK 10/QT/STB BG**

**PTK 10/QT/STB BG**

## Technical Data

---

### Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	2
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section single core (rigid)/stranded, max.	10 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	10 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	10 mm <sup>2</sup>
Wire cross-section AWG, min.	8
Wire cross-section AWG, max.	22
Stripping length	12 mm
Screw head	Slotted
Screw threading	M 4
Tightening torque, min.	1.2 Nm
Tightening torque, max.	2 Nm

1133.2

PTK 10/QT/STB BG

PTK 10/QT/STB BG

## Technical Data

---

### Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

### Further technical data

Mounting type	Mounting rail TS 35/7.5 and TS 32
Gauge plug acc. to EN 60 947-1	A5
End plate required	✓
Number of test pick-off options	2
Built-in test socket available	✓
Version of lengthwise partition	Sliding
Test sockets	2 x 0,4 mm Ø

**1133.2**

**PTK 10/QT/STB BG**

**PTK 10/QT/STB BG**

## Approvals

---

### CSA approval

---

CSA approval	C22.2 No 158
CSA approval granted	✓
CSA Usegroup C: rated voltage	600 V
CSA Usegroup C: rated current	45 A
CSA wire cross-section AWG, min.	22
CSA wire cross-section AWG, max.	8
CSA stripping length	12 mm
CSA torque, max.	2 Nm
CSA torque, min.	1.2 Nm

### CSAus approval

---

CSAus approval	UL 1059
CSAus approval granted	✓
CSAus Usegroup C: rated voltage	600 V
CSAus Usegroup C: rated current	45 A
CSAus wire cross-section AWG, min.	22
CSAus wire cross-section AWG, max.	8
CSAus stripping length	12 mm
CSAus torque, min.	1.2 Nm

1133.2

PTK 10/QT/STB BG

PTK 10/QT/STB BG

## Approvals

---

### CSAus approval

---

CSAus torque, max.

2 Nm

---



1133.2

PTK 10/QT/STB BG

PTK 10/QT/STB BG

Media

---



1133.2

PTK 10/QT/STB BG

PTK 10/QT/STB BG

## Accessories

---

### End plate

---



End plate, Width: 1.5 mm, Colour: Beige

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2782.2	AP L/Q/D	4044211055110	20 PC

### End bracket

---



End stop, Mounting type: Mounting rail TS 35/7.5,  
Width: 9.5 mm, Colour: Beige

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2828.0	ES 35/K/ST	4044211055547	50 PC



1133.2

PTK 10/QT/STB BG

PTK 10/QT/STB BG

## Accessories

---

### Short circuit plug

---



Short-circuit plug, Colour: Black

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2886.0	KSS 2-8	4044211056117	10 PC

---

### Test plug

---



Test plug, Colour: Red

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2051.0	PS 4	4044211048570	20 PC

---

1133.2

PTK 10/QT/STB BG

PTK 10/QT/STB BG

## Accessories

---

### Cross switch bridge

---



Cross-switch bridge, No. of poles: 2, Mounting type:  
Can be screwed on, Width: 14.8 mm, Colour: natural

---

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2783.0	QSB 2	4044211055127	20 PC

---



Cross-switch bridge, No. of poles: 3, Mounting type:  
Can be screwed on, Width: 22.9 mm, Colour: natural

---

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2784.0	QSB 3	4044211055134	20 PC

---

1133.2

PTK 10/QT/STB BG

PTK 10/QT/STB BG

## Accessories

---

### Cross switch bridge

---



Cross-switch bridge, No. of poles: 4, Mounting type: Can be screwed on, Width: 31 mm, Colour: natural

---


### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2785.0	QSB 4	4044211055141	20 PC

---

### Quick-marking

---



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 8 mm, Colour: White

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
9323.7	PMC SB 8/40 WH	4044211129231	400 PC

---

1133.2

PTK 10/QT/STB BG

PTK 10/QT/STB BG

## Accessories

---

### Screw driver

---



Screwdriver with bare blade, Colour: Black-grey

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1087.0	SDB 0,8x4,0	4044211014803	1 PC

---

### Insulation plate

---



Insulation plate, Colour: Beige

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2003.2	TRS 1	4044211048068	100 PC

---