

1523.2

FNAB 2,5

FNAB 2,5



M2.5



Five-wire mains-connection block, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm<sup>2</sup>, Colour: Multi-coloured

## Business data

Product description	Five-wire mains-connection block
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	43.31
Weight per piece (including packaging)	50.21
Unit of weight	G
Customs number	85369010
Country of origin	DE

## 1523.2 FNAB 2,5 FNAB 2,5

### Technical Data

---

#### Dimensions

---

Length	52 mm
Width	28 mm
Height TS 35/7.5	47 mm
Pitch	5 mm

#### Ratings

---

Rated voltage	800 V
Rated current	24 A
Rated cross-section	2.5 mm <sup>2</sup>
Rated impulse voltage	8 kV
Overvoltage category	III
Contamination degree	3

## 1523.2 FNAB 2,5 FNAB 2,5

### Technical Data

---

#### Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	10
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section single core (rigid)/stranded, max.	4 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	4 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm <sup>2</sup>
Wire cross-section AWG, min.	22
Wire cross-section AWG, max.	14
Stripping length	7 mm
Screw head	Slotted
Screw threading	M 2,5
Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.8 Nm

## 1523.2 FNAB 2,5 FNAB 2,5

### Technical Data

---

#### Materials

---

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

#### Further technical data

---

Mounting type	Mounting rail TS 35/7.5 and TS 32
Gauge plug acc. to EN 60 947-1	A3
Number of cross-connection channels	1
End plate required	✓
Number of test pick-off options	4

## 1523.2 FNAB 2,5 FNAB 2,5

### Approvals

---

#### Standards and regulations

---

EAC approval	TR ZU 004/2011
--------------	----------------

---

#### CSA approval

---

CSA approval	C22.2 No 158
--------------	--------------

---

CSA approval granted	✓
----------------------	---

---

CSA Usegroup C: rated voltage	600 V
-------------------------------	-------

---

CSA Usegroup C: rated current	20 A
-------------------------------	------

---

CSA wire cross-section AWG, min.	22
----------------------------------	----

---

CSA wire cross-section AWG, max.	14
----------------------------------	----

---

CSA stripping length	7 mm
----------------------	------

---

#### CSAus approval

---

CSAus approval	UL 1059
----------------	---------

---

CSAus approval granted	✓
------------------------	---

---

CSAus Usegroup C: rated voltage	600 V
---------------------------------	-------

---

CSAus Usegroup C: rated current	20 A
---------------------------------	------

---

CSAus wire cross-section AWG, min.	22
------------------------------------	----

---

CSAus wire cross-section AWG, max.	14
------------------------------------	----

---

**1523.2**

**FNAB 2,5**

**FNAB 2,5**

## Approvals

---

### CSAus approval

---

CSAus stripping length

7 mm

---


1523.2

FNAB 2,5

FNAB 2,5

Media

---



**M2.5**




**1523.2**  
**FNAB 2,5**  
**FNAB 2,5**

## Accessories

---

### End plate

---



End plate, Width: 1.5 mm, Colour: Beige

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2001.2	AP 2,5-10	4044211047979	50 PC

---

### End bracket

---



End stop, Mounting type: Mounting rail TS 35/7.5,  
Width: 9.5 mm, Colour: Beige

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2828.0	ES 35/K/ST	4044211055547	50 PC

---



## 1523.2 FNAB 2,5 FNAB 2,5

### Accessories

---

#### Test adapter

---



Test adapter, Length: 37.3 mm, Pitch size: 5 mm,  
Colour: Beige

---

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2812.0	TA 5/1/ST	4044211055394	10 PC

---

#### Cross connector

---



Cross-connector, No. of poles: 10, Mounting type: Can  
be screwed on, Width: 49.9 mm, Rated cross-section:  
2.5 mm<sup>2</sup>, Colour: natural

---

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2570.0	Q 10	4044211053604	10 PC

---


## 1523.2 FNAB 2,5 FNAB 2,5

### Accessories

---

#### Cross connector

---



Cross-connector, No. of poles: 2, Mounting type: Can be screwed on, Width: 9.1 mm, Rated cross-section: 2.5 mm<sup>2</sup>, Colour: natural

---

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2567.0	Q 2	4044211053574	50 PC

---



Cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 14.2 mm, Rated cross-section: 2.5 mm<sup>2</sup>, Colour: natural

---

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2568.0	Q 3	4044211053581	50 PC

---

## 1523.2 FNAB 2,5 FNAB 2,5

### Accessories

---

#### Cross connector

---



Cross-connector, No. of poles: 4, Mounting type: Can be screwed on, Width: 19.3 mm, Rated cross-section: 2.5 mm<sup>2</sup>, Colour: natural

---


#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2569.0	Q 4	4044211053598	20 PC

---

#### Quick-marking

---



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 5 mm, Colour: White

---

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4600.7	PMC SB 5/50 WH	4044211088903	500 PC

---

**1523.2**  
**FNAB 2,5**  
**FNAB 2,5**

## Accessories

---

### Screw driver

---



Screwdriver with bare blade, Colour: Black-grey

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1085.0	SDB 0,5x3,0	4044211014643	1 PC

---

### Insulation plate

---



Insulation plate, Colour: Beige

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2566.2	TRS 3	4044211053567	100 PC

---


**1523.2**  
**FNAB 2,5**  
**FNAB 2,5**

## Accessories

---

### Partition plate

---



Partition plate, Width: 1.5 mm, Colour: Beige

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2002.2	TW 2,5-10	4044211048044	50 PC

---