


17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm<sup>2</sup>, Width: 10 mm, Colour: Beige

## Business data

Product description	fused terminal
Packaging unit	25
Quantity unit	PC
Weight per piece (not including packaging)	25.2
Weight per piece (including packaging)	27.8
Unit of weight	G
Customs number	85369010
Country of origin	DE

**17043.2**

**SIK 10/Z/ST BG**

**SIK 10/Z/ST BG**

## Technical Data

---

### Dimensions

---

Length	60 mm
Width	10 mm
Height TS 35/7.5	73 mm
Height TS 32	69 mm

### Ratings

---

Rated voltage (determined by the illuminated display and fuse being used)	500 V
Rated current (as fuse-disconnect terminal)	10 A
Rated cross-section	10 mm <sup>2</sup>
Rated impulse voltage	8 kV
Overvoltage category	III
Contamination degree	3

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Technical Data

---

### Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	2 / disconnect-plug
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section single core (rigid)/stranded, max.	10 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	10 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	10 mm <sup>2</sup>
Wire cross-section AWG, min.	22
Wire cross-section AWG, max.	8
Stripping length	12 mm
Screw head	Slotted
Screw threading	M 4
Tightening torque, min.	1.2 Nm
Tightening torque, max.	2 Nm

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Technical Data

---

### Materials

---

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

### Further technical data

---

Mounting type	Mounting rail TS 35/7.5 and TS 32
---------------	-----------------------------------

Fuse size	6,3 x 25 / 6,3 x 32 mm
-----------	------------------------

Gauge plug acc. to EN 60 947-1	A5
--------------------------------	----

End plate required	✓
--------------------	---

Voltage fuse	250 V
--------------	-------

Version of fuse holder	Swivelling
------------------------	------------

Version of fuse cartridge	G fuse 6.3 x 25 / 6.3 x 32
---------------------------	----------------------------

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Approvals

---

### Standards and regulations

---

EAC approval	TR ZU 004/2011
--------------	----------------

EAC approval granted	✓
----------------------	---

Nemko approval	EN 60947-7-3
----------------	--------------

Nemko approval granted	✓
------------------------	---

### cUL Recognized

---

cUL Recognized	C22.2 No 158
----------------	--------------

cUL Recognized	✓
----------------	---

cUL Usegroup B: rated voltage	600 V
-------------------------------	-------

cUL Usegroup B: rated current	16 A
-------------------------------	------

cUL Usegroup C: rated voltage	600 V
-------------------------------	-------

cUL Usegroup C: rated current	16 A
-------------------------------	------

cUL wire cross-section single-core (rigid) AWG, min.	22
--	----

cUL wire cross-section single-core (rigid) AWG, max.	12
--	----

cUL wire cross-section stranded AWG, min.	22
---	----

cUL wire cross-section stranded AWG, max.	12
---	----

cUL torque	16 Nm
------------	-------

cUL wire material	Cu
-------------------	----

---

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Approvals

---

### German Lloyd approval

---

GL approval	IEC 60947-7-3
GL approval granted	✓
GL rated voltage	500 V
GL rated current	10 A
GL wire cross-section single core (rigid), min.	10 mm <sup>2</sup>

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Approvals

---

### KEMA KEUR approval

KEMA KEUR approval	EN 60947-7-3
KEMA KEUR approval granted	✓
KEMA rated voltage	500 V
KEMA voltage fuse, max.	250 V
KEMA rated current	10 A
KEMA rated impulse voltage	8 kV
KEMA wire cross-section single core (rigid), min.	2 mm <sup>2</sup>
KEMA wire cross-section single-core (rigid), max.	10 mm <sup>2</sup>
KEMA wire cross-section stranded, min.	2 mm <sup>2</sup>
KEMA wire cross-section stranded, max.	10 mm <sup>2</sup>
KEMA torque, min.	12 Nm
KEMA torque, max.	2 Nm
KEMA fuse size	6,3 x 25 / 6,3 x 32 mm
KEMA power loss in singular arrangement - overload and short-circuit protection, max.	2,5 / 2,5 W / A
KEMA power loss in compound arrangement - overload and short-circuit protection, max.	2,5 / 2,5 W / A
KEMA power loss in singular arrangement - only short-circuit protection, max.	4 / 10 W / A
KEMA power loss in compound arrangement - only short-circuit protection, max.	2,5 / 2,5 W / A

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Approvals

---

### UL Recognized

UL Recognized	UL 1059
UL Recognized granted	✓
UL Usegroup B: rated voltage	600 V
UL Usegroup B: rated current	16 A
UL Usegroup C: rated voltage	600 V
UL Usegroup C: rated current	16 A
UL wire cross-section single-core (rigid) AWG, min.	22
UL wire cross-section single-core (rigid) AWG, max.	12
UL wire cross-section stranded AWG, min.	22
UL wire cross-section stranded AWG, max.	12
UL torque	16 Lb In
UL wire material	Cu
UL factory wiring	✓
UL field wiring	✓




17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Media

---



**EAC**



17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

Media

---



17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Accessories

---

### External insulated cross-connector

---




External insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 98.9 mm, Rated current: 57 A; Colour: Yellow

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3994.8	AQI 10/10/18	4044211130428	10 PC

---



External insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 18.1 mm, Rated current: 57 A; Colour: Yellow

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3991.8	AQI 2/10/18	4044211130398	50 PC

---

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Accessories

---

### External insulated cross-connector

---



External insulated cross-connector, No. of poles: 3,  
Mounting type: Plug in, Width: 28.2 mm, Rated  
current: 57 A; Colour: Yellow

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3992.8	AQI 3/10/18	4044211130404	50 PC

---



External insulated cross-connector, No. of poles: 4,  
Mounting type: Plug in, Width: 38.3 mm, Rated  
current: 57 A; Colour: Yellow

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3993.8	AQI 4/10/18	4044211130411	50 PC

---

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Accessories

---

### External insulated cross-connector

---



External insulated cross-connector, No. of poles: 50, Mounting type: Plug in, Rated current: 57 A; Colour: Yellow

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3995.8	AQI 50/10/18	4044211137526	1 PC

---

### End bracket

---



End stop, Mounting type: Mounting rail TS 35/7.5, Width: 9.5 mm, Colour: Beige

#### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2828.0	ES 35/K/ST	4044211055547	50 PC

---

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Accessories

---

### Contact sleeve

---




Solid link, Colour: natural

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2497.0	KH 63 f. SIK 10/Z	4044211080976	50 PC

### LED-status display

---



Status display, Display: LED, Mounting type: Plug in, Colour: Beige

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1117.2	SST/SIK/2 LED`s(RD)/24V DC	4044211018047	10 PC

17043.2

SIK 10/Z/ST BG


SIK 10/Z/ST BG

## Accessories

---

### LED-status display

---




Status display, Display: LED, Mounting type: Plug in, Colour: Beige

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1116.2	SST/SIK/LED(RD)/115V DC/230V AC	4044211017972	10 PC

---



Status display, Display: LED, Mounting type: Plug in, Colour: Beige

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1113.2	SST/SIK/LED(RD)/12V DC/24V AC	4044211017682	10 PC

---

17043.2

SIK 10/Z/ST BG


SIK 10/Z/ST BG

## Accessories

---

### LED-status display

---




Status display, Display: LED, Mounting type: Plug in,  
Colour: Beige

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1114.2	SST/SIK/LED(RD)/20-30V DC/40-60V AC	4044211017897	10 PC

---



Status display, Display: LED, Mounting type: Plug in,  
Colour: Beige

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1115.2	SST/SIK/LED(RD)/40-60V DC/80-120V AC	4044211017965	10 PC

---



17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Accessories

---

### LED-status display

---




Status display, Display: LED, Mounting type: Plug in, Colour: Beige

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
17045.2	SST/SIK/LED(RD)/500 V AC/DC	4044211155834	25 PC

### Quick-marking

---



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 8 mm, Colour: White

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
9323.7	PMC SB 8/40 WH	4044211129231	400 PC

17043.2

SIK 10/Z/ST BG

SIK 10/Z/ST BG

## Accessories

---

### Screw driver

---



Screwdriver with bare blade, Colour: Black-grey

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1087.0	SDB 0,8x4,0	4044211014803	1 PC

---