


3221.3

FRK 4/3A OG

FRK 4/3A OG



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Orange

Business data

Product description	Feed-through terminal
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	13.4
Weight per piece (including packaging)	14.17
Unit of weight	G
Customs number	85369010
Country of origin	DE

3221.3

FRK 4/3A OG

FRK 4/3A OG

Technical Data

Dimensions

Length	64.3 mm
--------	---------

Width	6.1 mm
-------	--------

Height	42.3 mm
--------	---------

Height TS 35/7.5	43 mm
------------------	-------

Ratings

Rated voltage	800 V
---------------	-------

Rated current	32 A
---------------	------

Rated cross-section	4 mm ²
---------------------	-------------------

Rated impulse voltage	8 kV
-----------------------	------

Overvoltage category	III
----------------------	-----

Contamination degree	3
----------------------	---

3221.3

FRK 4/3A OG

FRK 4/3A OG

Technical Data

Connection data

Connection principle	Push-in connection
Connection position	Top
Connections	3
Number of terminals per level	3
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm ²
Wire cross-section single core (rigid)/stranded, max.	6 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	6 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	4 mm ²
Wire cross-section AWG, min.	20
Wire cross-section AWG, max.	10
Stripping length	12 mm

Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C

3221.3

FRK 4/3A OG

FRK 4/3A OG

Technical Data

Materials

Working temperature, max.	120 °C
---------------------------	--------

Further technical data

Mounting type	Mounting rail TS 35/7,5
---------------	-------------------------

Gauge plug acc. to EN 60 947-1	A4
--------------------------------	----

Number of cross-connection channels	2
-------------------------------------	---

End plate required	✓
--------------------	---

3221.3

FRK 4/3A OG

FRK 4/3A OG

Approvals

Standards and regulations

EAC approval	TR ZU 004/2011
--------------	----------------

EAC approval granted	✓
----------------------	---

CSA approval

CSA approval	C22.2 No 158
--------------	--------------

CSA approval granted	✓
----------------------	---

CSA Usegroup C: rated voltage	600 V
-------------------------------	-------

CSA Usegroup C: rated current	35 A
-------------------------------	------

CSA wire cross-section AWG, min.	26
----------------------------------	----

CSA wire cross-section AWG, max.	10
----------------------------------	----

CSA stripping length	12 mm
----------------------	-------

CSAus approval

CSAus approval	UL 1059
----------------	---------

CSAus approval granted	✓
------------------------	---

CSAus Usegroup C: rated voltage	600 V
---------------------------------	-------

CSAus Usegroup C: rated current	35 A
---------------------------------	------

CSAus wire cross-section AWG, min.	26
------------------------------------	----

3221.3

FRK 4/3A OG

FRK 4/3A OG

Approvals

CSAus approval

CSAus wire cross-section AWG, max.	10
CSAus stripping length	12 mm

KEMA KEUR approval

KEMA KEUR approval	EN 60947-7-1
KEMA KEUR approval granted	✓
KEMA rated voltage	800 V
KEMA rated current	32 A
KEMA rated impulse voltage	8 kV
KEMA wire cross-section single core (rigid), min.	0.2 mm ²
KEMA wire cross-section single-core (rigid), max.	6 mm ²
KEMA wire cross-section stranded, min.	0.2 mm ²
KEMA wire cross-section stranded, max.	6 mm ²

3221.3

FRK 4/3A OG

FRK 4/3A OG

Media



3221.3

FRK 4/3A OG

FRK 4/3A OG

Accessories

End plate



End plate, Width: 1.5 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3421.2	FAP 4/3A	4044211110529	20 PC

End bracket



End stop, Mounting type: Mounting rail TS 35/7.5 and TS 35/15, Width: 5 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3811.2	ZES 35/2	4044211080600	50 PC

3221.3

FRK 4/3A OG

FRK 4/3A OG

Accessories

Insulated cross connector



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 60.9 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3470.8	FQI 4/10	4044211110819	10 PC



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 12.1 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3472.8	FQI 4/2	4044211110826	50 PC

3221.3

FRK 4/3A OG

FRK 4/3A OG

Accessories


Insulated cross connector



Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 18.2 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3473.8	FQI 4/3	4044211110833	50 PC



Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 24.3 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3474.8	FQI 4/4	4044211110840	20 PC

3221.3

FRK 4/3A OG

FRK 4/3A OG

Accessories

Insulated cross connector



Insulated cross-connector, No. of poles: 5, Mounting type: Plug in, Width: 30.1 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3475.8	FQI 4/5	4044211110857	20 PC



Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 36.5 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3476.8	FQI 4/6	4044211110864	20 PC

3221.3

FRK 4/3A OG

FRK 4/3A OG

Accessories

Insulated cross connector



Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 42.6 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3477.8	FQI 4/7	4044211110871	20 PC



Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 48.7 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3478.8	FQI 4/8	4044211110888	10 PC

3221.3

FRK 4/3A OG

FRK 4/3A OG

Accessories

Insulated cross connector




Insulated cross-connector, No. of poles: 9, Mounting type: Plug in, Width: 54.8 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3479.8	FQI 4/9	4044211110895	10 PC

Quick-marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 6 mm, Colour: White

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4702.7	PMC SB 6/50 WH	4044211089986	500 PC

3221.3

FRK 4/3A OG

FRK 4/3A OG

Accessories

Screw driver



Screwdriver with bare blade, Colour: Black-grey

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1086.0	SDB 0,6x3,5	4044211014797	1 PC

Fourfold-cover



Cover, Length: 3.8 mm, Width: 23.6 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3427.8	FAD 4/4/B	4044211132941	20 PC