

3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Business data

Product description	Double-level terminals with electronic components
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	10
Weight per piece (including packaging)	10.8
Unit of weight	G
Customs number	85369010
Country of origin	DE

3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Technical Data

Dimensions

Length	83.6 mm
--------	---------

Width	5.1 mm
-------	--------

Height TS 35/7.5	39 mm
------------------	-------

Ratings

Rated voltage	24 V
---------------	------

Rated current	< 0,005 A
---------------	-----------

Rated cross-section	2.5 mm ²
---------------------	---------------------

Rated impulse voltage	8 kV
-----------------------	------

Overvoltage category	III
----------------------	-----

Contamination degree	3
----------------------	---

3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Technical Data

Connection data

Connection principle	Tension-spring connection
Connection position	Diagonal
Connections	2 x 2
Number of terminals per level	4
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.5 mm ²
Wire cross-section single core (rigid)/stranded, max.	4 mm ²
Wire cross-section stranded, min.	0.5 mm ²
Wire cross-section stranded, max.	4 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.5 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Wire cross-section AWG, min.	20
Wire cross-section AWG, max.	12
Stripping length	10 mm

Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C

3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Technical Data

Materials

Working temperature, max.	120 °C
---------------------------	--------

Further technical data

Mounting type	Mounting rail TS 35/7,5
---------------	-------------------------

Gauge plug acc. to EN 60 947-1	A3
--------------------------------	----

Number of cross-connection channels	1
-------------------------------------	---

End plate required	✓
--------------------	---

Number of test pick-off options	2
---------------------------------	---

Voltage illuminated display	24 V
-----------------------------	------

Cross-current via illuminated display	< 5 mA
---------------------------------------	--------

3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Approvals

Standards and regulations

EAC approval	TR ZU 004/2011
--------------	----------------

EAC approval granted	✓
----------------------	---

CSA approval

CSA approval	C22.2 No 158
--------------	--------------

CSA approval granted	✓
----------------------	---

CSA Usegroup C: rated voltage	24 V
-------------------------------	------

CSA Usegroup C: rated current	< 5 mA A
-------------------------------	----------

CSA wire cross-section AWG, min.	20
----------------------------------	----

CSA wire cross-section AWG, max.	12
----------------------------------	----

CSA stripping length	10 mm
----------------------	-------

CSAus approval

CSAus approval	UL 1059
----------------	---------

CSAus approval granted	✓
------------------------	---

CSAus Usegroup C: rated voltage	24 V
---------------------------------	------

CSAus Usegroup C: rated current	< 5 mA A
---------------------------------	----------

CSAus wire cross-section AWG, min.	20
------------------------------------	----

3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Approvals

CSAus approval

CSAus wire cross-section AWG, max.	12
CSAus stripping length	10 mm

KEMA KEUR approval

KEMA KEUR approval	EN 60947-7-1
KEMA KEUR approval granted	✓
KEMA rated voltage	24 V
KEMA rated current	- A
KEMA rated impulse voltage	8 kV
KEMA wire cross-section single core (rigid), min.	0.5 mm ²
KEMA wire cross-section single-core (rigid), max.	4 mm ²
KEMA wire cross-section stranded, min.	0.5 mm ²
KEMA wire cross-section stranded, max.	4 mm ²

3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Approvals

UL Recognized

UL Recognized	UL 1059
UL Recognized granted	✓
UL Usegroup B: rated voltage	24 V
UL Usegroup B: rated current	- A
UL Usegroup C: rated voltage	24 V
UL Usegroup C: rated current	- A
UL Usegroup D: rated voltage	24 V
UL Usegroup D: rated current	- A
UL wire cross-section single-core (rigid) AWG, min.	20
UL wire cross-section single-core (rigid) AWG, max.	12
UL wire cross-section stranded AWG, min.	20
UL wire cross-section stranded AWG, max.	12
UL wire material	Cu
UL factory wiring	✓
UL field wiring	✓

3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Media



3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Accessories

End plate



End plate, Width: 2 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3702.2	ZAP 2,5/4A	4044211060091	50 PC

Actuating tool



Actuating tool, No. of poles: 1, Colour: Black

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3808.0	BWMA 1 (0,5 x 3,5 mm)	4044211078850	1 PC


3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Accessories

End bracket



End stop, Mounting type: Mounting rail TS 35/7.5 and TS 35/15, Width: 6 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3748.2	ZES 35	4044211060572	50 PC

Test adapter



Test adapter, Pitch size: 5.1 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3740.2	ZTA 2,5	4044211060497	10 PC


3543.2

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

ZRK 2,5/2x2A/LED2(RD)/24V DC BG

Accessories

Quick-marking



Terminal marker / Pocket Maxicard, Length: 5 mm,
Width: 5 mm, Colour: White

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4600.7	PMC SB 5/50 WH	4044211088903	500 PC

Fourfold-cover



Cover, Length: 6.7 mm, Width: 20.4 mm, Colour:
Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3706.0	ZAD 2,5/4/B	4044211060244	20 PC
