


3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Business data

Product description	Feed-through terminal
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	7.2
Weight per piece (including packaging)	8.06
Unit of weight	G
Customs number	85369010
Country of origin	DE

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Technical Data

Dimensions

Length	52 mm
Width	5.1 mm
Height TS 15/5.5	34 mm
Height TS 15 / 5.5 with BA	44 mm

Ratings

Rated voltage	800 V
Rated current	24 A
Rated cross-section	2.5 mm ²
Rated impulse voltage	8 kV
Overvoltage category	III
Contamination degree	3

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Technical Data

Connection data

Connection principle	Tension-spring connection
Connection position	Diagonal
Connections	3
Number of terminals per level	3
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.5 mm ²
Wire cross-section single core (rigid)/stranded, max.	4 mm ²
Wire cross-section stranded, min.	0.5 mm ²
Wire cross-section stranded, max.	4 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.5 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Wire cross-section AWG, min.	20
Wire cross-section AWG, max.	12
Stripping length	10 mm

Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Technical Data

Materials

Working temperature, max.	120 °C
---------------------------	--------

Further technical data

Mounting type	TS 15
---------------	-------

Gauge plug acc. to EN 60 947-1	A3
--------------------------------	----

Number of cross-connection channels	1
-------------------------------------	---

End plate required	✓
--------------------	---

Number of test pick-off options	2
---------------------------------	---

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Approvals

Standards and regulations

EAC approval	TR ZU 004/2011
--------------	----------------

EAC approval granted	✓
----------------------	---

CSA approval

CSA approval	C22.2 No 158
--------------	--------------

CSA approval granted	✓
----------------------	---

CSA Usegroup C: rated voltage	300 V
-------------------------------	-------

CSA Usegroup C: rated current	20 A
-------------------------------	------

CSA wire cross-section AWG, min.	20
----------------------------------	----

CSA wire cross-section AWG, max.	12
----------------------------------	----

CSA stripping length	10 mm
----------------------	-------

CSAus approval

CSAus approval	UL 1059
----------------	---------

CSAus approval granted	✓
------------------------	---

CSAus Usegroup C: rated voltage	300 V
---------------------------------	-------

CSAus Usegroup C: rated current	20 A
---------------------------------	------

CSAus wire cross-section AWG, min.	20
------------------------------------	----

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Approvals

CSAus approval

CSAus wire cross-section AWG, max.	12
CSAus stripping length	10 mm

cUL Recognized

cUL Recognized	C22.2 No 158
cUL Recognized	✓
cUL Usegroup B: rated voltage	300 V
cUL Usegroup B: rated current	20 A
cUL Usegroup C: rated voltage	300 V
cUL Usegroup C: rated current	20 A
cUL Usegroup D: rated voltage	300 V
cUL Usegroup D: rated current	20 A
cUL wire cross-section single-core (rigid) AWG, min.	20
cUL wire cross-section single-core (rigid) AWG, max.	12
cUL wire cross-section stranded AWG, min.	20
cUL wire cross-section stranded AWG, max.	12
cUL wire material	Cu

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Approvals

KEMA KEUR approval

KEMA KEUR approval	EN 60947-7-1
KEMA KEUR approval granted	✓
KEMA rated voltage	800 V
KEMA rated current	24 A
KEMA rated impulse voltage	8 kV
KEMA wire cross-section single core (rigid), min.	0.5 mm ²
KEMA wire cross-section single-core (rigid), max.	4 mm ²
KEMA wire cross-section stranded, min.	0.5 mm ²
KEMA wire cross-section stranded, max.	4 mm ²

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Approvals

UL Recognized


UL Recognized	UL 1059
UL Recognized granted	✓
UL Usegroup B: rated voltage	300 V
UL Usegroup B: rated current	20 A
UL Usegroup C: rated voltage	300 V
UL Usegroup C: rated current	20 A
UL Usegroup D: rated voltage	300 V
UL Usegroup D: rated current	20 A
UL wire cross-section single-core (rigid) AWG, min.	20
UL wire cross-section single-core (rigid) AWG, max.	12
UL wire cross-section stranded AWG, min.	20
UL wire cross-section stranded AWG, max.	12
UL wire material	Cu
UL factory wiring	✓
UL field wiring	✓

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Media




3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Accessories

End plate



End plate, Width: 1.6 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3794.2	ZAP SR 3A/15	4044211061234	50 PC

Actuating tool



Actuating tool, No. of poles: 1, Colour: Black

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3808.0	BWMA 1 (0,5 x 3,5 mm)	4044211078850	1 PC

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Accessories

End bracket



End stop, Mounting type: Mounting rail TS 15/5.5,
Width: 5 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3812.2	ZES 15	4044211080617	50 PC

Test adapter



Test adapter, Pitch size: 5.1 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3740.2	ZTA 2,5	4044211060497	10 PC

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Accessories


Insulated cross connector



Insulated cross-connector, No. of poles: 99, Mounting type: Plug in, Width: 500 mm, Rated cross-section: 2.5 mm², Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3719.8	ZQI 2,5/0,5 m/99 poles	4044211060374	2 PC



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 49.9 mm, Rated cross-section: 2.5 mm², Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3718.8	ZQI 2,5/10	4044211060367	10 PC

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Accessories

Insulated cross connector



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 9.1 mm, Rated cross-section: 2.5 mm², Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3710.8	ZQI 2,5/2	4044211060282	50 PC



Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 14.2 mm, Rated cross-section: 2.5 mm², Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3711.8	ZQI 2,5/3	4044211060299	50 PC

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Accessories

Insulated cross connector



Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 19.3 mm, Rated cross-section: 2.5 mm², Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3712.8	ZQI 2,5/4	4044211060305	20 PC



Insulated cross-connector, No. of poles: 5, Mounting type: Plug in, Width: 24.4 mm, Rated cross-section: 2.5 mm², Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3713.8	ZQI 2,5/5	4044211060312	20 PC

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Accessories

Insulated cross connector



Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 29.5 mm, Rated cross-section: 2.5 mm², Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3714.8	ZQI 2,5/6	4044211060329	20 PC



Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 34.6 mm, Rated cross-section: 2.5 mm², Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3715.8	ZQI 2,5/7	4044211060336	20 PC

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Accessories

Insulated cross connector




Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 39.7 mm, Rated cross-section: 2.5 mm², Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3716.8	ZQI 2,5/8	4044211060343	10 PC

Quick-marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 5 mm, Colour: White

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4600.7	PMC SB 5/50 WH	4044211088903	500 PC

3599.2

ZSRK 2,5/3A/15 BG

ZSRK 2,5/3A/15 BG

Accessories

Fourfold-cover



Cover, Length: 6.7 mm, Width: 20.4 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3706.0	ZAD 2,5/4/B	4044211060244	20 PC
