

4969.0

SI 6,3x32 8,000 A/T

SI 6,3x32 8,000A-T



Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 500 / 440 / 250 V, Rated current: 8 A

Business data

Product description	fuse
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.96
Weight per piece (including packaging)	1
Unit of weight	G
Customs number	85361010
Country of origin	EEC

4969.0

SI 6,3x32 8,000 A/T

SI 6,3x32 8,000A-T

Technical Data

Dimensions

Length	31.8 mm
Diameter of contact cap	6.35 mm
Dimensions	6,3x32 mm

Ratings

Rated voltage	500 / 440 / 250 V
Rated current	8 A

Materials

Contact caps	Brass
Surface	Nickel
Tube	Ceramic

Further technical data

Trigger characteristic	Time-lag (T)
Rated breaking capacity	1,5 kA @ AC 500 (cosφ = 1 10 kA @ AC 440 V cosφ = 0,3)
Voltage drop	110 mV

Datasheet



4969.0

SI 6,3x32 8,000 A/T

SI 6,3x32 8,000A-T

Technical Data

Further technical data

Power loss (@ 1.5 In)	2.6 W
Melting integral I ² ts	370 A ² s
