

6 5 4 3 2 1

APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/6/20	

Top view of the crimp housing. Dimension A is the distance between the centers of adjacent crimp positions. Dimension B is the total width of the housing. A specific dimension of .118 [3.00] is shown between the centers of two crimp positions. The height of the housing is .152 [3.86].

Side view of the crimp housing. The height of the housing is .559 [14.20].

Side view of the crimp housing showing the latching mechanism.

Positions: 02 thru 24

A = .118 [3.00] x No. of Space

B = .118 [3.00] x No. of Space + .157 [4.00]

SPECIFICATIONS:

Material:
Insulator: Glass-Filled Polyimide, rated UL 94V-0
Insulator color: Black

Electrical:
Voltage rating: 250 V AC/DC
Current rating: 5 A AC/DC
Contact resistance: 10 mohms max
Insulation resistance: 1000 Mohms min
Dielectric withstanding voltage: 1500 VAC for 1 minute

Environmental:
Lead free, RoHS compliant

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		ADAM 909 Rahway Avenue, TECH Union, NJ 07083 INTERCONNECTS Phone: 908-687-5000 Fax: 908-687-5710	
INCHES		HOLES	
.X ± .10	∅X ± .10	TITLE .118" [3.00mm] CRIMP HOUSING, SINGLE ROW LATCHING TYPE, HALOGEN-FREE	
.XX ± .020	∅XX ± .015		
.XXX ± .015	∅XXX ± .010		
APPROVALS		DATE	
DRAWN	LH	3/6/20	
CHECKED	AY1	3/6/20	
APPROVED			
SIZE X	PART NO. DMT-D-1-XX	REF: S00015T	SCALE: NTS
REV. -	SHEET 1 OF 1		

6 5 4 3 2 1