

6 5 4 3 2 1

APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/26/18	

D
C
B
A

RECOMMENDED PCB LAYOUT

01P 02P 03P 04P xxP

WITHOUT COVER

SPECIFICATIONS:

Material:
Insulator: PA, rated UL 94V-0
Insulator color: Green
Contact: Copper Alloy
Electrical:
Voltage rating: 600 V
Current rating: 40 A
Dielectric withstanding voltage: 2,200 VAC for 1 minute
Mechanical:
Strip length: 15~16mm
Wire Range: 24~8 AWG
Temperature Rating:
Operating temperature: -40°C to +105°C
Environmental:
Lead free, RoHS compliant.

Poles: 01 thru XXP
A = .295 [7.50] X No. of Positions +.071 [1.80]
B = .295 [7.50] X No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		ADAM TECH		909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
INCHES		HOLES		TITLE	
.X ± .10	Ø.X ± .10	SPRING CLAMP EURO BLOCK, .295 [7.50] PITCH			
.XX ± .020	Ø.XX ± .015	APPROVALS		DATE	
.XXX ± .015	Ø.XXX ± .010	DRAWN	AY	11/26/18	
		CHECKED	AC	11/26/18	
		APPROVED			
SIZE	PART NO.	REF:	S00067C	SCALE:	NTS
X	EB167A-XX-M	SHEET	1 OF 1		

6 5 4 3 2 1