



MODEL NO.	H	MODEL NO.	H
TC-00104-00	4.30	TC-00104F-00	8.00
TC-00104A-00	5.00	TC-00104G-00	12.50
TC-00104B-00	7.30	TC-00104H-00	13.50
TC-00104C-00	9.50	TC-00104I-00	11.00
TC-00104D-00	13.00	TC-00104J-00	12.00
TC-00104E-00	7.00	TC-00104L-00	6.00
		TC-00104R-00	16.00

5	CONTACT	P B S	1	Ag PLATED
3	TERMINAL	BRASS	4	Ag PLATED
1	FRAME	NYLON	1	
NO	PART	MATERIAL	QTY	REMARKS

4	COVER BOARD	POLYESTER FILM	1	
2	KNOB	NYLON	1	
NO	PART	MATERIAL	QTY	REMARKS

ISSUED	SPECIFICATION	TITLE: TACT SWITCH			
	RATING: DC 12V 50mA	MODEL NO: TC-00104 ()-00			
	CONTACT RESISTANCE: 100mΩ Max.				
	INSULATION RESISTANCE: 100MΩ at 500V DC	TOLERANCE	UNIT: MM	DWN.	<i>hoo</i>
	WITHSTAND VOLTAGE: AC 250V for 1 minute.	UP TO 1.0:±0.1	SCALE: 4:1	CHK'D.	<i>hoo</i>
	OPERATION FORCE: REFER ATTACH SPECIFICATION	1.0 TO 10.0:±0.2	VERSION: 06	APPD.	<i>hoo</i>
	SWITCHING LIFE: 100k Cycles Min.	OVER 10.0:±0.3	DRWG NO:		
BY: <i>hoo</i>	VIMEX INTERNATIONAL CORPORATION				
DATE: 04-MAR-2008					



Product Specification

Part Number **TC-00104-00**

- 1) **Rating:** **DC 12V 50mA**
- 2) **Operating Temperature Range:** **-10°C ~ +60°C**
- 3) **Electrical Performance:**

	Test Conditions	Performance
Contact Resistance	Measured at small current (10mA 1000Hz or less)	100mΩ Max.
Insulation Resistance	Shall be measured by applying 500V DC, between all terminals and between the terminals and the frame for 1minute±5sec.	100MΩ Min.
Dielectric Strength	AC 250v rms (50-60Hz) for 1 minute trip current: 0.5 mA 1. Between Terminals 2. Between individual terminals and frame	Without damage to parts arcing or breakdown

4) **Mechanical Performance:**

	Test Conditions	Performance
Operating Force	Measuring push the top of the actuator (knob)	160gf±70gf (130gf±30gf)
Terminal Strength	A static load of 300gf shall be applied to the terminal for 15 sec. in any direction.	Electrical characteristics shall be satisfied without damage of excessive looseness of terminals.
Displacement of Actuator (Knob)	A static load of 5N (500gf) shall be applied to the top of the actuator (knob) and then displacement shall be measured to the direction of the arrow.	The lever shall have no serious deformation and function is normally.
Life Test	Endurance without loading: A switch shall be subjected to 100,000 cycles at a speed of 15 to 18 cycles per minute without loading.	(1) Contact resistance: 200mΩ Max. (2) Insulation Resistance: 50MΩ Min. (3) Withstand Voltage: AC 250V for 1 minute. (4) Operating force: Less than +10%~-30% of initial operating force (5) Without damage to parts arcing or breakdown ect.

5) Environmental Characteristics:

	Test Conditions	Performance
Soldering Test	The top of terminals shall be dipped 2mm in the solder bath of $245\pm 5^{\circ}\text{C}$ for 3 ± 0.5 seconds.	The area of soldering should be over 75%
Soldering heat resistance	Solder bath method: Solder temperature $255\pm 5^{\circ}\text{C}$. Immersion time within 5 seconds. Immersion depth up to the surface of the board 0.8mm dimensions of component holes in the printed wiring board shall be in accordance with those specified in this specification. Solder Iron method: Temperature of solder $350\pm 10^{\circ}\text{C}$. Time of solder 3 ± 0.5 seconds.	Without deformation of case or excessive looseness of terminals electrical characteristics shall be satisfied
Cold test	The switch shall be stored at a temperature of $-25\pm 3^{\circ}\text{C}$ for 48 hours, then the switch shall be maintained at standard atmospheric conditions for 1 hour after which measurement shall be made	There shall be no deformation or cracks in molded part
Heat test	The switch shall be stored at a temperature of $70\pm 2^{\circ}\text{C}$ for 48 hours, then the switch shall be maintained at standard atmospheric conditions for 1 hour after which measurement shall be made	
Humidity test	The switch shall be stored at a temperature of $40\pm 2^{\circ}$ and a humidity of 90% to 95% for 48 hours, then the switch shall be maintained at a standard atmospheric conditions for 1 hour after which measurement shall be made	There shall be no deformation or cracks in molded part.
Test Condition (Unless otherwise specified) Temperature: 5°C - 35°C Humidity: 45% - 85% R.H. Pressure: 86-106kPa		