

DC AXIAL FAN 60x60x38mm (Stator Outlet Blade)



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
 Lead Wire: UL Type #26 AWG
 Weight: 95 g Packing: 100PCS/CTN



ES IP SF

- High Airflow
- High Static Pressure

DC Axial Fans

Model Number	Voltage (VDC)	Op. Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6038B12W3-81 ★	12	8.0~13.8	29.80	8.00	51.70	5,000	260	3.12	B	①
FD6038B12W5-81 ★	12	8.0~13.8	35.40	11.40	56.20	6,000	390	4.68	B	②
FD6038B12W7-81 ★	12	8.0~13.8	42.00	15.50	59.60	7,000	680	8.16	B	③
FD6038B24W3-81 ★	24	18.0~27.6	29.80	8.00	51.70	5,000	170	4.08	B	①
FD6038B24W5-81 ★	24	18.0~27.6	35.40	11.40	56.20	6,000	200	4.80	B	②
FD6038B24W7-81 ★	24	18.0~27.6	42.00	15.50	59.60	7,000	320	7.68	B	③
FD6038B24W9-81 ★	24	18.0~27.6	50.60	18.00	63.00	8,000	390	9.36	B	④

• If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

