

DC AXIAL FAN 70x70x15mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
Lead Wire: UL Type #26 AWG
Weight: 57 g **Packing:** 300PCS/CTN



DC Axial Fans

Model Number		Voltage (VDC)	Op. Voltage (VDC)	AirFlow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD7015B12W1-81	★	12	8.0~13.8	11.30	0.60	10.30	1,400	50	0.60	B,L,S	①
FD7015B12W2-81	★	12	8.0~13.8	16.70	1.20	18.70	2,000	80	0.96	B,L,S	②
FD7015B12W3-81		12	6.0~13.8	22.30	2.00	26.10	2,600	90	1.08	B,L,S	③
FD7015B12W5-81		12	6.0~13.8	27.70	2.90	31.50	3,200	150	1.80	B,L,S	④
FD7015B12W7-81		12	6.0~13.8	33.50	4.00	36.00	3,800	240	2.88	B,L,S	⑤

- For "Long Life" or "Sleeve" bearing versions, change the "B" in the model number to "L" or "S" respectively.
- If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

