

DC AXIAL FAN 60x60x25mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame
Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
Lead Wire: UL Type #24 AWG
Weight: 79 g **Packing:** 200PCS/CTN



ES

SF



DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6025B12W3-84	★▲ 12	6.0~13.8	29.20	10.60	40.40	5,500	170	2.04	B	①
FD6025B12W5-84	★▲ 12	6.0~13.8	31.70	13.20	42.40	6,100	210	2.52	B	②
FD6025B12W7-84	★▲ 12	6.0~13.2	36.80	17.20	47.30	7,000	320	3.84	B	③

- For "Fluid Lubricant " bearing version, change the "B" in the model number to "F".
- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

