



| | |
|-------------------------|-------------------------|
| Mounting hole (inch) | 0.2362" |
| Mounting hole (metric) | 6mm |
| Indicator type | standard |
| Mounting type | with bezel |
| Bezel type | superflat |
| Bezel material | metal |
| Bezel color | matt chrome |
| Bezel size | M6 |
| Protection | IP40 |
| Lens type | flat |
| Lens color | green diffused |
| Lens size | 3mm |
| Connector Tpe | tab terminals 2.0x0.5mm |
| Connector number | 2 |
| Connector for lamp test | no |
| Number LED chip | 1 |
| Indicator color | green |
| Dom wave length | 568nm |
| Peak Wave Lenght (mA) | |
| Op. voltage (V) | 12V DC |
| Forward volt max. | |
| Rectifier | - |
| AC current | - |
| DC current | 20mA |
| Lum in min (mcd) | |
| Lum in type (DC) | 8mcd |
| Voltage tolerance (%) | 10% |
| Op. temperature (°C) | -25°C...+60°C |

| | | | |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ | Datasheet : 1900 | Print date : 05/05/06 |
| Revision : | Revision date : 2006-03-15 | Name : ROJ | Scale : |



Part Number : 19002251
Serial Number : 1900
LEDs Indicators

| | |
|--------------------------|---------------|
| Storage temperature (°C) | -25°C...+60°C |
| Narrative | |
| Viewing angle (°) | |

| | | | |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ | Datasheet : 1900 | Print date : 05/05/06 |
| Revision : | Revision date : 2006-03-15 | Name : ROJ | Scale : |