



Mounting hole (inch)	0.2362"
Mounting hole (metric)	6mm
Indicator type	standard
Mounting type	with bezel
Bezel type	superflat
Bezel material	metal
Bezel color	matt chrome
Bezel size	M6
Protection	IP40
Lens type	flat
Lens color	red diffused
Lens size	3mm
Connector Tpe	tab terminals 2.0x0.5mm
Connector number	2
Connector for lamp test	no
Number LED chip	1
Indicator color	red
Dom wave length	625nm
Peak Wave Lenght (mA)	
Op. voltage (V)	12V DC
Forward volt max.	
Rectifier	-
AC current	-
DC current	20mA
Lum in min (mcd)	
Lum in type (DC)	13mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1900	Print date : 05/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19002253
Serial Number : 1900
LEDs Indicators

Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1900	Print date : 05/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :