



|                         |                         |
|-------------------------|-------------------------|
| Mounting hole (inch)    | 0.2362"                 |
| Mounting hole (metric)  | 6mm                     |
| Indicator type          | bi-color                |
| Mounting type           | with bezel              |
| Bezel type              | recessed                |
| Bezel material          | metal                   |
| Bezel color             | black chrome            |
| Bezel size              | M6                      |
| Protection              | IP40                    |
| Lens type               | round                   |
| Lens color              | white diffused          |
| Lens size               | 3mm                     |
| Connector Tpe           | tab terminals 2.0x0.5mm |
| Connector number        | 2                       |
| Connector for lamp test | no                      |
| Number LED chip         | 2                       |
| Indicator color         | green/yellow            |
| Dom wave length         | 568nm/588nm             |
| Peak Wave Lenght (mA)   |                         |
| Op. voltage (V)         | 24V DC                  |
| Forward volt max.       |                         |
| Rectifier               | -                       |
| AC current              | -                       |
| DC current              | 15mA                    |
| Lum in min (mcd)        |                         |

|             |                            |                  |                       |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ                 | Datasheet : 1903 | Print date : 07/05/06 |
| Revision :  | Revision date : 2006-03-15 | Name : ROJ       | Scale :               |



Part Number : 19031356  
Serial Number : 1903  
LEDs Indicators

|                                 |               |
|---------------------------------|---------------|
| <b>Lum in type (DC)</b>         | 30/15mcd      |
| <b>Voltage tolerance (%)</b>    | 10%           |
| <b>Op. temperature (°C)</b>     | -25°C...+60°C |
| <b>Storage temperature (°C)</b> | -25°C...+60°C |
| <b>Narrative</b>                |               |
| <b>Viewing angle (°)</b>        |               |

|             |                            |                  |                       |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ                 | Datasheet : 1903 | Print date : 07/05/06 |
| Revision :  | Revision date : 2006-03-15 | Name : ROJ       | Scale :               |