



Mounting hole (inch)	0.3150"
Mounting hole (metric)	8mm
Indicator type	standard
Mounting type	with bezel
Bezel type	prominent
Bezel material	metal
Bezel color	black chrome
Bezel size	M8
Protection	IP40
Lens type	round
Lens color	red diffused
Lens size	5mm
Connector Tpe	leads of LEDs
Connector number	2

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1904	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19041020
 Serial Number : 1904
 LEDs Indicators

Connector for lamp test	no
Number LED chip	1
Indicator color	red
Dom wave length	625nm
Peak Wave Lenght (mA)	
Op. voltage (V)	without resistor
Forward volt max.	
Rectifier	-
AC current	-
DC current	20mA
Lum in min (mcd)	
Lum in type (DC)	80mcd
Voltage tolerance (%)	-
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	removable LEDs
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1904	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :