



Mounting hole (inch)	0.3150"
Mounting hole (metric)	8mm
Indicator type	flashing
Mounting type	with bezel
Bezel type	prominent
Bezel material	metal
Bezel color	matt chrome
Bezel size	M8
Protection	IP40
Lens type	round
Lens color	yellow diffused
Lens size	5mm
Connector Tpe	leads of LEDs
Connector number	2
Connector for lamp test	no
Number LED chip	1
Indicator color	yellow
Dom wave length	588nm
Peak Wave Lenght (mA)	
Op. voltage (V)	3.5-13V DC
Forward volt max.	
Rectifier	-
AC current	-
DC current	38-56mA
Lum in min (mcd)	
Lum in type (DC)	32mcd

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1904	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19062002
Serial Number : 1904
LEDs Indicators

Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1904	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :