



Mounting hole (inch)	0.3150"
Mounting hole (metric)	8mm
Indicator type	flashing
Mounting type	with bezel
Bezel type	recessed
Bezel material	metal
Bezel color	matt chrome
Bezel size	M8
Protection	IP40
Lens type	round
Lens color	green diffused
Lens size	5mm
Connector Tpe	tab terminals 2.8x0.8mm
Connector number	2
Connector for lamp test	no
Number LED chip	1
Indicator color	green
Dom wave length	568nm
Peak Wave Lenght (mA)	
Op. voltage (V)	24V DC
Forward volt max.	
Rectifier	-
AC current	-
DC current	38-56mA
Lum in min (mcd)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1905	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19072351
Serial Number : 1905
LEDs Indicators

Lum in type (DC)	32mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1905	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :