



| | |
|-------------------------|-------------------------|
| Mounting hole (inch) | 0.3150" |
| Mounting hole (metric) | 8mm |
| Indicator type | tri-color |
| Mounting type | with bezel |
| Bezel type | superflat |
| Bezel material | metal |
| Bezel color | matt chrome |
| Bezel size | M8 |
| Protection | IP40 |
| Lens type | flat |
| Lens color | white diffused |
| Lens size | 5mm |
| Connector Tpe | tab terminals 2.0x0.5mm |
| Connector number | 3 |
| Connector for lamp test | no |
| Number LED chip | 2 |
| Indicator color | red/green/yellow |
| Dom wave length | 625nm/568nm |
| Peak Wave Lenght (mA) | |

| | | | |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ | Datasheet : 1910 | Print date : 08/05/06 |
| Revision : | Revision date : 2006-03-15 | Name : ROJ | Scale : |



Part Number : 19102354
 Serial Number : 1910
 LEDs Indicators

| | |
|---------------------------------|---------------|
| Op. voltage (V) | 24V DC |
| Forward volt max. | |
| Rectifier | |
| AC current | |
| DC current | 15/15/30mA |
| Lum in min (mcd) | |
| Lum in type (DC) | 3/3/6mcd |
| Voltage tolerance (%) | 10% |
| Op. temperature (°C) | -25°C...+60°C |
| Storage temperature (°C) | -25°C...+60°C |
| Narrative | |
| Viewing angle (°) | |

| | | | |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ | Datasheet : 1910 | Print date : 08/05/06 |
| Revision : | Revision date : 2006-03-15 | Name : ROJ | Scale : |