



Mounting hole (inch)	0.5512"
Mounting hole (metric)	14mm
Indicator type	flashing
Mounting type	with bezel
Bezel type	prominent
Bezel material	metal
Bezel color	matt chrome
Bezel size	M14
Protection	IP40
Lens type	round
Lens color	yellow diffused
Lens size	10mm
Connector Tpe	leads of LEDs
Connector number	2
Connector for lamp test	no
Number LED chip	1
Indicator color	yellow
Dom wave length	588nm
Peak Wave Lenght (mA)	
Op. voltage (V)	3.5-13V DC
Forward volt max.	
Rectifier	-
AC current	-

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1922	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19222002  
Serial Number : 1922  
LEDs Indicators

<b>DC current</b>	38-56mA
<b>Lum in min (mcd)</b>	
<b>Lum in type (DC)</b>	70mcd
<b>Voltage tolerance (%)</b>	10%
<b>Op. temperature (°C)</b>	-25°C...+60°C
<b>Storage temperature (°C)</b>	-25°C...+60°C
<b>Narrative</b>	
<b>Viewing angle (°)</b>	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1922	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :