



Mounting hole (inch)	0.5512"
Mounting hole (metric)	14mm
Indicator type	flashing
Mounting type	with bezel
Bezel type	prominent
Bezel material	metal
Bezel color	matt chrome
Bezel size	M14
Protection	IP40
Lens type	round
Lens color	red diffused
Lens size	10mm
Connector Tpe	tab terminals 2.8x0.8
Connector number	2
Connector for lamp test	no
Number LED chip	1
Indicator color	red
Dom wave length	625nm
Peak Wave Lenght (mA)	
Op. voltage (V)	24V DC
Forward volt max.	
Rectifier	-
AC current	-
DC current	38-56mA

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1922	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19222035
Serial Number : 1922
LEDs Indicators

Lum in min (mcd)	
Lum in type (DC)	100mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1922	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :