



(Anode / anode) +  + (Anode / anode)

Mounting hole (inch)	0.5512"
Mounting hole (metric)	14mm
Indicator type	standard
Mounting type	with bezel
Bezel type	prominent
Bezel material	metal
Bezel color	black chrome
Bezel size	M14
Protection	IP67
Lens type	round
Lens color	red diffused
Lens size	10mm
Connector Tpe	tab terminals 2.8x0.8
Connector number	3
Connector for lamp test	yes
Number LED chip	1
Indicator color	red

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1927	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19271350
 Serial Number : 1927
 LEDs Indicators

Dom wave length	625nm
Peak Wave Length (mA)	
Op. voltage (V)	24V AC/DC
Forward volt max.	
Rectifier	Half Wave
AC current	9mA
DC current	17mA
Lum in min (mcd)	
Lum in type (DC)	80mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1927	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :