



(Anode / anode) + + (Anode / anode)

Mounting hole (inch)	0.5512"
Mounting hole (metric)	14mm
Indicator type	standard
Mounting type	with bezel
Bezel type	prominent
Bezel material	metal
Bezel color	matt chrome
Bezel size	M14
Protection	IP67
Lens type	round
Lens color	green diffused
Lens size	10mm
Connector Tpe	tab terminals 2.8x0.8
Connector number	3
Connector for lamp test	yes
Number LED chip	1
Indicator color	green

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1927	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19272351
 Serial Number : 1927
 LEDs Indicators

Dom wave length	568nm
Peak Wave Length (mA)	
Op. voltage (V)	24V AC/DC
Forward volt max.	
Rectifier	Half Wave
AC current	9mA
DC current	17mA
Lum in min (mcd)	
Lum in type (DC)	60mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1927	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :