



| | |
|-------------------------|-----------------------|
| Mounting hole (inch) | 10.2362" |
| Mounting hole (metric) | 16mm |
| Indicator type | standard |
| Mounting type | with bezel |
| Bezel type | prominent |
| Bezel material | plastic |
| Bezel color | black |
| Bezel size | M16 |
| Protection | IP67 |
| Lens type | round |
| Lens color | yellow diffused |
| Lens size | 10mm |
| Connector Tpe | tab terminals 2.8x0.8 |
| Connector number | 2 |
| Connector for lamp test | no |
| Number LED chip | 1 |
| Indicator color | yellow |
| Dom wave length | 587nm |
| Peak Wave Lenght (mA) | |
| Op. voltage (V) | 12V AC/DC |
| Forward volt max. | |
| Rectifier | Half Wave |

| | | | |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ | Datasheet : 1937 | Print date : 08/05/06 |
| Revision : | Revision date : 2006-03-15 | Name : ROJ | Scale : |



Part Number : 19371252
Serial Number : 1937
LEDs Indicators

| | |
|---------------------------------|---------------|
| AC current | 8mA |
| DC current | 16mA |
| Lum in min (mcd) | |
| Lum in type (DC) | 1000mcd |
| Voltage tolerance (%) | 10% |
| Op. temperature (°C) | -25°C...+60°C |
| Storage temperature (°C) | -25°C...+60°C |
| Narrative | |
| Viewing angle (°) | |

| | | | |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ | Datasheet : 1937 | Print date : 08/05/06 |
| Revision : | Revision date : 2006-03-15 | Name : ROJ | Scale : |