



Mounting hole (inch)	10.2362"
Mounting hole (metric)	16mm
Indicator type	standard
Mounting type	with bezel
Bezel type	prominent
Bezel material	metal
Bezel color	matt chrome
Bezel size	M16
Protection	IP67
Lens type	conical
Lens color	white diffused
Lens size	10mm
Connector Tpe	tab terminals 2.8x0.8

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1942	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 1942213WM
 Serial Number : 1942
 LEDs Indicators

Connector number	2
Connector for lamp test	no
Number LED chip	1
Indicator color	white
Dom wave length	0.31 / 0.32
Peak Wave Lenght (mA)	
Op. voltage (V)	130V AC
Forward volt max.	
Rectifier	Half Wave
AC current	6mA
DC current	-
Lum in min (mcd)	
Lum in type (DC)	270mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	with protection tube
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1942	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :