



Mounting hole (inch)	0.1969"
Mounting hole (metric)	5mm
Indicator type	standard
Mounting type	flush mounting
Bezel type	-
Bezel material	-
Bezel color	-
Bezel size	-
Protection	IP40
Lens type	round
Lens color	red diffused
Lens size	5mm
Connector Tpe	tab terminals 2.8x0.8
Connector number	2
Connector for lamp test	no
Number LED chip	1
Indicator color	red
Dom wave length	625nm
Peak Wave Lenght (mA)	
Op. voltage (V)	24V DC
Forward volt max.	
Rectifier	-

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1959	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19592353
Serial Number : 1959
LEDs Indicators

AC current	-
DC current	22mA
Lum in min (mcd)	
Lum in type (DC)	11mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	FBE 1-4
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 1959	Print date : 08/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :