



Mounting hole (inch)	0.8661"
Mounting hole (metric)	22mm
Indicator type	standard
Mounting type	with bezel
Bezel type	prominent
Bezel material	metal
Bezel color	satın chrome
Bezel size	M22
Protection	IP67
Lens type	round
Lens color	blue diffused
Lens size	16mm
Connector Tpe	tab terminals 2.8x0.8
Connector number	3
Connector for lamp test	no
Number LED chip	1

Drawn : ROJ	Ch'd : ROJ	Datasheet : 195A	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 195A0257MUC
 Serial Number : 195A
 LEDs Indicators

Indicator color	blue
Dom wave length	470nm
Peak Wave Lenght (mA)	
Op. voltage (V)	12V AC/DC
Forward volt max.	
Rectifier	Bridge
AC current	16mA
DC current	16mA
Lum in min (mcd)	
Lum in type (DC)	280mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 195A	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :