



Mounting hole (inch)	0.8661"
Mounting hole (metric)	22mm
Indicator type	standard
Mounting type	with bezel
Bezel type	prominent
Bezel material	plastic
Bezel color	black
Bezel size	M22
Protection	IP67
Lens type	round
Lens color	green diffused
Lens size	16mm
Connector Tpe	tab terminals 2.8x0.8
Connector number	3
Connector for lamp test	no

Drawn : ROJ	Ch'd : ROJ	Datasheet : 195A	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 195A1351UC
 Serial Number : 195A
 LEDs Indicators

Number LED chip	1
Indicator color	green
Dom wave length	525nm
Peak Wave Lenght (mA)	
Op. voltage (V)	24V AC/DC
Forward volt max.	
Rectifier	Bridge
AC current	16mA
DC current	16mA
Lum in min (mcd)	
Lum in type (DC)	400mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 195A	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :