



| | |
|------------------------|-----------------------|
| Mounting hole (inch) | 0.8661" |
| Mounting hole (metric) | 22mm |
| Indicator type | standard |
| Mounting type | with bezel |
| Bezel type | prominent |
| Bezel material | metal |
| Bezel color | black chrome |
| Bezel size | M22 |
| Protection | IP67 |
| Lens type | round |
| Lens color | red diffused |
| Lens size | 16mm |
| Connector Tpe | tab terminals 2.8x0.8 |

| | | | |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ | Datasheet : 195E | Print date : 11/05/06 |
| Revision : | Revision date : 2006-03-15 | Name : ROJ | Scale : |



Part Number : 195E1130M
 Serial Number : 195E
 LEDs Indicators

| | |
|--------------------------|----------------------|
| Connector number | 3 |
| Connector for lamp test | no |
| Number LED chip | 6 |
| Indicator color | red |
| Dom wave length | 620nm |
| Peak Wave Lenght (mA) | |
| Op. voltage (V) | 130V AC |
| Forward volt max. | |
| Rectifier | Half Wave |
| AC current | 6mA |
| DC current | - |
| Lum in min (mcd) | |
| Lum in type (DC) | 60mcd |
| Voltage tolerance (%) | 10% |
| Op. temperature (°C) | -25°C...+60°C |
| Storage temperature (°C) | -25°C...+60°C |
| Narrative | with protection tube |
| Viewing angle (°) | |

| | | | |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ | Datasheet : 195E | Print date : 11/05/06 |
| Revision : | Revision date : 2006-03-15 | Name : ROJ | Scale : |