



|                               |                       |
|-------------------------------|-----------------------|
| <b>Mounting hole (inch)</b>   | 0.8661"               |
| <b>Mounting hole (metric)</b> | 22mm                  |
| <b>Indicator type</b>         | standard              |
| <b>Mounting type</b>          | with bezel            |
| <b>Bezel type</b>             | prominent             |
| <b>Bezel material</b>         | plastic               |
| <b>Bezel color</b>            | black                 |
| <b>Bezel size</b>             | M22                   |
| <b>Protection</b>             | IP67                  |
| <b>Lens type</b>              | flat                  |
| <b>Lens color</b>             | white diffused        |
| <b>Lens size</b>              | 16mm                  |
| <b>Connector Tpe</b>          | tab terminals 2.8x0.8 |

|                    |                                   |                         |                              |
|--------------------|-----------------------------------|-------------------------|------------------------------|
| <b>Drawn : ROJ</b> | <b>Ch'd : ROJ</b>                 | <b>Datasheet : 195F</b> | <b>Print date : 11/05/06</b> |
| <b>Revision :</b>  | <b>Revision date : 2006-03-15</b> | <b>Name : ROJ</b>       | <b>Scale :</b>               |



Part Number : 195F113W  
 Serial Number : 195F  
 LEDs Indicators

|                          |                      |
|--------------------------|----------------------|
| Connector number         | 3                    |
| Connector for lamp test  | no                   |
| Number LED chip          | 1                    |
| Indicator color          | white                |
| Dom wave length          | 0.31 / 0.32          |
| Peak Wave Lenght (mA)    |                      |
| Op. voltage (V)          | 130V AC              |
| Forward volt max.        |                      |
| Rectifier                | Half Wave            |
| AC current               | 6mA                  |
| DC current               | -                    |
| Lum in min (mcd)         |                      |
| Lum in type (DC)         | 130mcd               |
| Voltage tolerance (%)    | 10%                  |
| Op. temperature (°C)     | -25°C...+60°C        |
| Storage temperature (°C) | -25°C...+60°C        |
| Narrative                | with protection tube |
| Viewing angle (°)        |                      |

|             |                            |                  |                       |
|-------------|----------------------------|------------------|-----------------------|
| Drawn : ROJ | Ch'd : ROJ                 | Datasheet : 195F | Print date : 11/05/06 |
| Revision :  | Revision date : 2006-03-15 | Name : ROJ       | Scale :               |