



Mounting hole (inch)	0.3150"
Mounting hole (metric)	8mm
Indicator type	tri-color
Mounting type	with bezel
Bezel type	recessed
Bezel material	metal
Bezel color	matt chrome
Bezel size	M8
Protection	IP40
Lens type	round
Lens color	white diffused
Lens size	5mm
Connector Tpe	tab terminals 2.0x0.5mm
Connector number	3
Connector for lamp test	no
Number LED chip	2
Indicator color	red/green/yellow

Drawn : ROJ	Ch'd : ROJ	Datasheet : 19TRxl	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :



Part Number : 19TR2I12
 Serial Number : 19TRxl
 LEDs Indicators

Dom wave length	625nm/568nm
Peak Wave Length (mA)	
Op. voltage (V)	12V DC
Forward volt max.	
Rectifier	-
AC current	-
DC current	20/20/40mA
Lum in min (mcd)	
Lum in type (DC)	10/20/30mcd
Voltage tolerance (%)	10%
Op. temperature (°C)	-25°C...+60°C
Storage temperature (°C)	-25°C...+60°C
Narrative	
Viewing angle (°)	

Drawn : ROJ	Ch'd : ROJ	Datasheet : 19TRxl	Print date : 11/05/06
Revision :	Revision date : 2006-03-15	Name : ROJ	Scale :