



All dimensions are in millimeters / Tolerance is +/- 0.25 unless otherwise noted

Emitting Color: green

Chip: GaP

Lens Color: water clear

RoHS compliant

Electrical / Optical Characteristics at Ta=25°C

Symbol	Parameter	Min.	Typ.	Max.	Conditions
$2\Theta_{1/2}$	Viewing Angle		120°		
I_v	Luminous Intensity	10mcd	25mcd		$I_F = 20mA$
λ_{peak}	Peak Wavelength		565nm		$I_F = 20mA$
λ_{dom}	Dominant Wavelength		568nm		$I_F = 20mA$
$\Delta\lambda_{1/2}$	Spectral Line Half Width		30nm		$I_F = 20mA$
V_F	Forward Voltage		2.2V	2.5V	$I_F = 20mA$
I_R	Reverse Current			10µA	$V_R = 5V$
C	Capacitance		15pF		$V_F = 0V; f = 1MHz$

Absolute Maximum Ratings at Ta=25°C

Parameter	
Power Dissipation	62.5mW
DC Forward Current	25mA
Peak Forward Current (1)	140mA
Reverse Voltage	5V
Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C
Reflow Soldering Temperature	260°C for 10 seconds

Notes: (1) 1/10 duty cycle, 0.1ms pulse width



CML Technologies GmbH & Co. KG
D-67098 Bad Dürkheim

SMD LED - green

Revision:	Date:	Name:	Scale: 8 : 1	Drawn: J.J.	Ch'd: D.L.	Date: 06.04.06
			Datasheet: CS100G20C-C0			