



All dimensions are in millimeters / Tolerance is +/- 0.25 unless otherwise noted

**Emitting Colour: yellow**

**Chip: GaAsP / GaP**

**Epoxy: yellow diffused**

**RoHS compliant**

**Electrical / Optical Characteristics at Ta=25°C**

Symbol	Parameter	Min.	Typ.	Max.	Conditions
$2\Theta_{1/2}$	Viewing Angle		40°		
$I_v$	Luminous Intensity	5mcd	15mcd		$I_F = 10\text{mA}$
$\lambda_{\text{peak}}$	Peak Wavelength		590nm		$I_F = 20\text{mA}$
$\lambda_{\text{dom}}$	Dominant Wavelength		588nm		$I_F = 20\text{mA}$
$\Delta\lambda_{1/2}$	Spectral Line Half Width		35nm		$I_F = 20\text{mA}$
$V_F$	Forward Voltage		2.1V	2.5V	$I_F = 20\text{mA}$
$I_R$	Reverse Current			10µA	$V_R = 5\text{V}$
C	Capacitance		20pF		$V_F = 0\text{V}; f = 1\text{MHz}$

**Absolute Maximum Ratings at Ta=25°C**

Parameter	
Power Dissipation	105mW
DC Forward Current	30mA
Peak Forward Current (1)	140mA
Reverse Voltage	5V
Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C
Lead Solder Temperature (2)	260°C for 3 seconds

Notes: (1) 1/10 duty cycle, 0.1ms pulse width / (2) 2mm below package base



CML Technologies GmbH & Co. KG  
D-67098 Bad Dürkheim

**T-1 (3mm) LED - yellow**

				Drawn: <b>J.J.</b>	Ch'd: <b>D.L.</b>	Date: <b>17.10.05</b>
Revision:	Date:	Name:	Scale: <b>3 : 1</b>	Datasheet: <b>CT301Y08D-40</b>		