



All dimensions are in millimeters / Tolerance is +/- 0.25 unless otherwise noted

Emitting Colour: blue

Chip: InGaN

Epoxy: water clear

RoHS compliant

Electrical / Optical Characteristics at Ta=25°C

Symbol	Parameter	Min.	Typ.	Max.	Conditions
$2\Theta_{1/2}$	Viewing Angle		16°		
I_v	Luminous Intensity	650mcd	1200mcd		$I_F = 20mA$
λ_{peak}	Peak Wavelength		465nm		$I_F = 20mA$
λ_{dom}	Dominant Wavelength		470nm		$I_F = 20mA$
$\Delta\lambda_{1/2}$	Spectral Line Half Width		25nm		$I_F = 20mA$
V_F	Forward Voltage		3.7V	4.3V	$I_F = 20mA$
I_R	Reverse Current			10µA	$V_R = 5V$
C	Capacitance		110pF		$V_F = 0V; f = 1MHz$

Absolute Maximum Ratings at Ta=25°C

Parameter	
Power Dissipation	120mW
DC Forward Current	30mA
Peak Forward Current (1)	160mA
Reverse Voltage	5V
Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C
Lead Solder Temperature (2)	260°C for 3 seconds

Notes: (1) 1/10 duty cycle, 0.1ms pulse width / (2) 2mm below package base



CML Technologies GmbH & Co. KG
D-67098 Bad Dürkheim

T-1 3/4 (5mm) LED - blue

Revision:	Date:	Name:	Scale: 3 : 1	Drawn: J.J.	Ch'd: D.L.	Date: 17.10.05
			Datasheet: CT501B16C-16			