

ARCA AR1085CHFL



Order symbol: AR1085CHFL EAN:

w/Plastic quick release latch.

Product nbr:8561656El. number:Description:PC EnclosureFinland:Remarks:Hinged opaque flat cover

Including: Hinged cover. Base with 10-32 brass inserts, latched flat cover with formed in place PUR gasket, and stainless hinge pin. Quick release latches. (Latch options available.). Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

Sample photo

Dimensions:	Length	Width	Height	Accessories:	
mm:	254	203	127	ALBP108	Aluminur
inch:	10.0	8.0	5.0	ADFP108	Dead Fro
mon.	10.0	0.0	0.0	ASP108	Aluminur
Materials:				ASPK108	Swing Pa
Material:	Polycarbonate			ASPHK10	Swing Pa

Material: Polycarbonate

Base colour: RAL 7035 -light grey

Cover screws material: Stainless steel

Cover colour: RAL 7035 -light grey

Gasket material: Polyurethane

Temperatures:

Temperature °C (short term): -40 ... 140 °C
Temperature °C (continuous): -40 ... 80 °C
Temperature °F (short term): -40 ... 284 °F
Temperature °F (continuous): -40 ... 175 °F

Accessories:

ABP108 Painted Steel Back Panel

Accessories.		
ALBP108	Aluminum Back Panel	
ADFP108	Dead Front Panel w/ screws	
ASP108	Aluminum Swing Panel	
ASPK108	Swing Panel Kit incl. Panel	
ASPHK10	Swing Panel Kit w/o Panel	
AMFL8	8" Mounting Flange Set	

6418074098290

Rating

Ingress Protection (EN 60529): IP66/IP67 Impact Resistance (EN 62262): IK09 Electrical insulation: Totally insulated Halogen free (DIN/VDE 0472, Part 815): 1

Flammability Rating: UL 508 Glow Wire Test (IEC 695-2-1) °C: 960 NEMA Class: NEMA 4, 4X, 6, 6P, 12, 13

Certificates:

UV resistance: UL 508

Gost R

